



PREMIUM PLUS with STYLE® Faux Glaze No.748

This unique, water-based translucent product is designed for blending with BEHR PREMIUM PLUS® Interior paints and applied using decorative paint applicators. This mixture extends the paint's open time allowing you to create dynamic faux-painted finishes and unique decorative wall designs.



Where To Use

Properly painted Interior surfaces. Ideal for Family Rooms, Living Rooms, Dining Rooms, Bedrooms, Kids' Rooms, Hallways, Kitchens, Bathrooms, Doors, Trim and Ceilings.

Preparation†

Remove loose paint, wash off any dirt and grease with detergent, remove mildew stains with a product such as BEHR® MILDEW STAIN REMOVER NO. 62. Rinse and allow to dry.

Scuff sand glossy surfaces.

Countersink nailheads, repair imperfections and sand smooth.

Remove all dust with a damp cloth, allow to dry.

Allow new stucco, plaster and masonry to cure 30 days before priming.

Use a product such as BEHR ENAMEL UNDERCOATER PRIMER & SEALER NO. 75.

Apply Interior Eggshell, Satin or Semi-Gloss sheen for the base color according to label instructions.

Mixing The Glaze Color

In a plastic container, blend 1 part paint (1 quart) to 4 parts glaze (1 gallon) for each selected glaze color. Stir glaze mixture until thoroughly blended and occasionally during application.

Application

Refer to the BEHR Glazing Accents Colors & Techniques Guide and www.behr.com for additional instructions on application. Using the appropriate tool and technique, apply the glaze color over the dried base color. Work in 3' x 3' (90 x 90 cm) areas or smaller, depending on technique. Blend from section to section in a random pattern, maintaining a wet edge to ensure smooth transitions. Typical coverage is 400 sq. ft. (37 m²) per gallon. Coverage may vary depending upon the surface and desired effect. For maximum protection over the finish, after the glaze color has dried a minimum of 48 hours, apply a product such as BEHR CRYSTAL CLEAR WATER-BASED POLYURETHANE NO. 780.

Dry Time

Dries to touch in 1 hour at 75°F (24°C) and 50% humidity. Allow 4 hours to dry between coats.

Longer dry time required in cooler temperatures and in higher humidity.

After 30 days, surface is fully cured and may be cleaned with a mild, non-abrasive liquid detergent.

Clean Up & Storage

Wash tools with soap and water.

Wipe excess product from lip of container prior to sealing to keep glaze from gluing lid closed.

Dried spills must be cleaned with lacquer thinner or paint remover.

Properly dispose of all soiled rags and protect unused product from freezing.

To recycle or properly dispose of paint in your community call 1-800-CLEANUP (U.S.A. only) or visit www.Earth911.org.

LIMITED WARRANTY

Behr Process Corporation warrants that this product meets Behr's manufacturing specifications. If this product does not meet these specifications, Behr will, at its option and upon proof of purchase, either furnish an equivalent amount of new product to you or refund the purchase price of this product. **Behr will not be responsible for (1) labor or the cost of labor for removal or application of any product; or (2) any incidental or consequential damages, whether based on breach of express or implied warranty, negligence, strict liability or any other legal theory.** Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights and you may also have other rights, which vary from state to state.

Refer to the BEHR PREMIUM PLUS WITH STYLE® Faux Glazing Colors & Techniques Guide for additional tips or visit us at www.behr.com for expert project advice and perfect color coordination with COLORSMART BY BEHR™.

To consult with a BEHR Certified Coatings Professional, call 1-800-854-0133 Ext. 2 (U.S.A. only).

©2008 BEHR PROCESS CORPORATION
Santa Ana, CA 92704 U.S.A.

†WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

WARNING! This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

WARNING! IRRITANT! HARMFUL IF SWALLOWED. CONTAINS: ETHYLENE GLYCOL. MAY CAUSE EYE, NOSE AND THROAT IRRITATION. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING OF VAPORS AND SPRAY MIST. WEAR EYE PROTECTION AND PROTECTIVE CLOTHING. USE ONLY WITH ADEQUATE VENTILATION. To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air. If properly used, a respirator (NIOSH approved for organic vapor with P series particulate pre-filter) may offer additional protection; obtain professional advice before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. FIRST AID: If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

CAUTION: KEEP OUT OF REACH OF CHILDREN - DO NOT TAKE INTERNALLY.





PREMIUM PLUS with STYLE® BELLAGIO FAUX™ No. 725

This exciting new finish was inspired by old world European faux finishes. Bellagio Faux is durable, easy to apply and touch up, and has a sophisticated washed look. It is used on top of a base color of BEHR PREMIUM PLUS® Interior Flat Enamel paint.



Where To Use

Properly painted Interior surfaces. Ideal for Family Rooms, Living Rooms, Bedrooms, Kitchens, Bathrooms, Offices and Hallways.

Preparation†

Remove loose paint, wash off any dirt and grease with detergent, remove mildew stains with a product such as BEHR® MILDEW STAIN REMOVER NO. 62. Rinse and allow to dry.

Countersink nailheads, repair imperfections and sand smooth.

Scuff sand glossy surfaces.

Remove all dust with a damp cloth, allow to dry.

Allow plaster and masonry to cure 30 days before priming.

If priming is necessary, use a product such as BEHR ENAMEL UNDERCOATER PRIMER & SEALER NO. 75.

Apply a product such as tinted BEHR PREMIUM PLUS® Interior Flat Enamel paint for base color according to label instructions.

Application

Refer to the BEHR BELLAGIO FAUX™ Colors & Techniques Guide and www.behr.com for additional instructions on application. Dry time recommendations are based on 77°F (25°C) and 50% humidity and will vary depending on the air temperature/humidity and how thick the product is applied.

Use product on smooth to lightly textured surfaces. DO NOT THIN. Typical coverage is 250-350 sq. ft. (23-33 m²) per gallon.

Generously apply BELLAGIO FAUX using the BEHR BELLAGIO FAUX BRUSH NO. 722 or a nylon/polyester brush. Use random "X" like strokes to fill in a 3 x 3' (90 x 90 cm) section.

Allow section to set for 15-18 minutes (7-10 minutes if mixed with LUMINOSO™) until the BELLAGIO FAUX begins to lose the wet look.

Use soft "X" like strokes to smooth down the product with the BEHR BELLAGIO FAUX TROWEL NO. 721.

Repeat this process in 3 x 3' sections until your entire surface is complete.

Allow 4 hours to dry if a second top color of BELLAGIO FAUX is being applied. Apply second top color repeating first top color instructions. Allow the second top color to set for 7-10 minutes (15-18 minutes if first top color is mixed with Metallic) before smoothing down with a trowel.

Dry Time

At 77°F (25°C) and 50% humidity: dries to touch in 1 hour, allow 4 hours to dry if applying a second top color. Longer dry time required in cooler temperatures and in higher humidity.

After 30 days, the surface is fully cured and may be cleaned with a mild, non-abrasive liquid detergent.

Dry paint film is mildew resistant.

Clean Up & Storage

Wash tools with soap and water.

Properly dispose of all soiled rags and protect unused product from freezing.

To recycle or properly dispose of paint in your community call 1-800-CLEANUP (U.S.A. only) or visit www.Earth911.org.

LIMITED WARRANTY

Behr Process Corporation warrants that this product meets Behr's manufacturing specifications. If this product does not meet these specifications, Behr will, at its option and upon proof of purchase, either furnish an equivalent amount of new product to you or refund the purchase price of this product. **Behr will not be responsible for (1) labor or the cost of labor for removal or application of any product; or (2) any incidental or consequential damages, whether based on breach of express or implied warranty, negligence, strict liability or any other legal theory.** Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights and you may also have other rights, which vary from state to state.

Refer to the BEHR PREMIUM PLUS WITH STYLE® BELLAGIO FAUX Colors & Techniques Guide for additional tips or visit us at www.behr.com for expert project advice and perfect color coordination with COLORSMART BY BEHR™.

To consult with a BEHR Certified Coatings Professional, call 1-800-854-0133 Ext. 2 (U.S.A. only).

©2008 BEHR PROCESS CORPORATION
Santa Ana, CA 92704 U.S.A.

†WARNING! If you scrape sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

WARNING! This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

WARNING! IRRITANT! HARMFUL IF SWALLOWED. CONTAINS: TEXANOL. MAY CAUSE EYE, NOSE AND THROAT IRRITATION. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING OF VAPORS AND SPRAY MIST. WEAR EYE PROTECTION AND PROTECTIVE CLOTHING. USE ONLY WITH ADEQUATE VENTILATION. To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air. If properly used, a respirator (NIOSH approved for organic vapor with P series particulate pre-filter) may offer additional protection; obtain professional advice before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. FIRST AID: If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

CAUTION: KEEP OUT OF REACH OF CHILDREN - DO NOT TAKE INTERNALLY





PREMIUM PLUS with STYLE® SandWash No.760

This 100% Acrylic, water-based coating uses a mixture of white, black and clear beads to create a stone and sand texture. Apply 2 coats using a 3/4" lambswool/polyester nap roller cover.



Where To Use

Previously painted or prepared Interior surfaces. Ideal for Bedrooms, Family Rooms, Dens and Ceilings.

Preparation†

Remove loose paint, wash off any dirt and grease with detergent, remove mildew stains with a product such as BEHR® MILDEW STAIN REMOVER NO. 62. Rinse and allow to dry.

Scuff sand glossy surfaces.

Countersink nailheads, repair imperfections and sand smooth.

Remove all dust with a damp cloth, allow to dry.

Allow new stucco, plaster and masonry to cure 30 days.

Use BEHR SANDWASH FOUNDATION NO. 765.

Have the SANDWASH FOUNDATION tinted close to the SANDWASH color you have selected.

Application

Refer to the BEHR Faux Textures Colors & Techniques Guide and www.behr.com for additional instructions on application. Use product when the surface and air temperatures are between 50-90°F (10-32°C). DO NOT THIN. Typical coverage is 150-200 sq. ft. (14-19 m²) per gallon.

FIRST COAT:

Apply SANDWASH in 2 x 2' (60 x 60 cm) sections.

Begin at the top corner and use a nylon/polyester brush to paint a 2 ft. (60 cm) strip across the ceiling edge and down the corner of the wall.

Thoroughly saturate a premium quality 3/4" lambswool/polyester nap roller with product and fill in the 2 x 2' (60 x 60 cm) area that has just been cut in.

Overlap sections slightly, continuing to cut-in (where necessary) and roll 2 ft. (60 cm) sections down the wall. Keeping a wet edge will help decrease the likelihood of lap marks.

When column is complete, apply a thin coat of SANDWASH over the entire column area. Repeat this process across the entire wall. The first coat will not provide complete coverage and full effect.

SECOND COAT:

Apply second coat repeating the first coat instructions.

If applying in high traffic or high moisture areas, use a product such as BEHR CRYSTAL CLEAR WATER-BASED POLYURETHANE NO. 780. Apply after the SANDWASH finish has cured 7 days. The topcoat will darken the tone and/or color of the finish.

Dry Time

Dries to the touch in 2 hours at 75°F (24°C) and 50% humidity.

Allow to dry at least 4 hours between coats. Additional dry time is needed in cooler temperatures and in higher humidity.

Allow up to 7 days to dry for uniform appearance and 2 weeks before cleaning with a soft cloth and mild, non-abrasive liquid detergent.

Clean Up & Storage

Wash tools with soap and water.

Properly dispose of all soiled rags and protect unused product from freezing.

To recycle or properly dispose of paint in your community call 1-800-CLEANUP (U.S.A. only) or visit www.Earth911.org.

LIMITED WARRANTY

Behr Process Corporation warrants that this product meets Behr's manufacturing specifications. If this product does not meet these specifications, Behr will, at its option and upon proof of purchase, either furnish an equivalent amount of new product to you or refund the purchase price of this product. **Behr will not be responsible for (1) labor or the cost of labor for removal or application of any product; or (2) any incidental or consequential damages, whether based on breach of express or implied warranty, negligence, strict liability or any other legal theory.** Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights and you may also have other rights, which vary from state to state.

Refer to the BEHR PREMIUM PLUS WITH STYLE® Faux Textures Colors & Techniques Guide for additional tips or visit us at www.behr.com for expert project advice and perfect color coordination with COLORSMART BY BEHR™.

To consult with a BEHR Certified Coatings Professional, call 1-800-854-0133 Ext. 2 (U.S.A. only).

©2008 BEHR PROCESS CORPORATION
Santa Ana, CA 92704 U.S.A.

†WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

WARNING! This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

WARNING! IRRITANT! HARMFUL IF SWALLOWED. CONTAINS: ETHYLENE GLYCOL. MAY CAUSE EYE, NOSE AND THROAT IRRITATION. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING OF VAPORS AND SPRAY MIST. WEAR EYE PROTECTION AND PROTECTIVE CLOTHING. USE ONLY WITH ADEQUATE VENTILATION. To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air. If properly used, a respirator (NIOSH approved for organic vapor with P series particulate pre-filter) may offer additional protection; obtain professional advice before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. FIRST AID: If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

CAUTION: KEEP OUT OF REACH OF CHILDREN - DO NOT TAKE INTERNALLY.





PREMIUM PLUS with STYLE® SandWash Foundation No.765

This 100% Acrylic Latex product provides the ideal foundation for BEHR® SandWash. Have the product tinted close to the selected SandWash color.



Where To Use

As a basecoat on all new and previously painted Interior surfaces where SANDWASH will be used.

Preparation†

Remove loose paint, wash off any dirt and grease with detergent, remove mildew stains with a product such as BEHR® MILDEW STAIN REMOVER NO. 62.

Scuff sand glossy surfaces.

Countersink nailheads, repair imperfections and sand smooth.

Remove all dust with a damp cloth, allow to dry.

Allow new stucco, plaster and masonry to cure for 30 days prior to application.

Application

Use product when the surface and air temperatures are between 50-90°F (10-32°C).

Use a high quality 3/8-1/2" nap roller cover, nylon/polyester brush or an airless sprayer (.015 spray tip).

Coverage is 250-400 sq. ft. (23-37 m²) per gallon depending on the surface texture, porosity and application method.

Stir occasionally. Do not thin if using a roller or brush; however, if using a sprayer and thinning is required, thin with water at a rate of no more than 1/2 pint per gallon.

Have product tinted close to topcoat color with no more than 6 ounces of colorant per gallon.

Dry Time

Can be topcoated in 1 hour at 77°F (25°C) and 50% humidity. Longer dry time required in cooler temperatures and in higher humidity.

Clean Up & Storage

Use soap and water.

Properly dispose of all soiled rags and protect unused product from freezing.

To recycle or properly dispose of paint in your community call 1-800-CLEANUP (U.S.A. only) or visit www.Earth911.org.

LIMITED WARRANTY

Behr Process Corporation warrants that this product meets Behr's manufacturing specifications. If this product does not meet these specifications, Behr will, at its option and upon proof of purchase,

either furnish an equivalent amount of new product to you or refund the purchase price of this product. **Behr will not be responsible for (1) labor or the cost of labor for removal or application of any product; or (2) any incidental or consequential damages, whether based on breach of express or implied warranty, negligence, strict liability or any other legal theory.** Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights and you may also have other rights, which vary from state to state.

Refer to the BEHR PREMIUM PLUS WITH STYLE® Faux Textures Colors and Techniques Guide for additional tips or visit us at www.behr.com for expert project advice and perfect color coordination with COLORSMART BY BEHR™.

To consult with a BEHR Certified Coatings Professional, call 1-800-854-0133 Ext. 2 (U.S.A. only).

©2008 BEHR PROCESS CORPORATION
Santa Ana, CA 92704 U.S.A.

†WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

WARNING! This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

WARNING! IRRITANT! HARMFUL IF SWALLOWED. CONTAINS: ETHYLENE GLYCOL. MAY CAUSE EYE, NOSE AND THROAT IRRITATION. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING OF VAPORS AND SPRAY MIST. WEAR EYE PROTECTION AND PROTECTIVE CLOTHING. USE ONLY WITH ADEQUATE VENTILATION. To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air. If properly used, a respirator (NIOSH approved for organic vapor with P series particulate pre-filter) may offer additional protection; obtain professional advice before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. FIRST AID: If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

CAUTION: KEEP OUT OF REACH OF CHILDREN - DO NOT TAKE INTERNALLY.





PREMIUM PLUS with STYLE® Venetian Plaster No.770

Create an old-world European feel with Venetian Plaster. This heavy-bodied, water-based product is applied with a trowel and can be burnished for a marble-like appearance. Available in 24 designer colors or custom matched to coordinate with your décor.



Where To Use

Previously painted or primed Interior surfaces. Ideal for areas such as: Living Rooms, Dining Rooms, Bedrooms, Offices, Hallways and Ceilings.

Preparation†

Remove loose paint, wash off any dirt and grease with detergent, remove mildew stains with a product such as BEHR® MILDEW STAIN REMOVER NO. 62. Rinse and allow to dry.

Scuff-sand glossy surfaces.

Countersink nailheads, repair imperfections and sand smooth.

Remove all dust with a damp cloth, allow to dry.

Allow new stucco, plaster and masonry to cure 30 days before priming.

Use a product such as BEHR ENAMEL UNDERCOATER PRIMER & SEALER NO. 75.

Application

Refer to the BEHR Faux Textures Colors & Techniques Guide and www.behr.com for additional instructions on application. Use product on smooth surface when the surface and air temperatures are between 50-90°F (10-32°C). DO NOT THIN. Typical coverage is 150 sq. ft. (14 m²) per gallon with 2 coat application.

First Coat:

Apply product using a straight-edged, flexible steel trowel or wall scraper. Hold trowel at a 15-30° angle, spreading a thin layer of the product across the surface. Complete coverage is not necessary.

Allow to dry approximately 4 hours.

Second Coat:

Hold trowel at a 60-90° angle to the surface, spreading a thin layer of the product, filling in the empty areas.

After the second coat has dried at least 24 hours, a polished effect can be created by sanding the surface with 400 or 600 grit sandpaper, removing the plaster dust and then rubbing the surface with the flat side of the steel trowel.

In high moisture or high traffic areas, apply BEHR VENETIAN PLASTER TOPCOAT NO. 775 over the Venetian Plaster finish without burnishing. Topcoat dries to a satin sheen.

Dry Time

Allow first coat to dry 4 hours.

If burnishing, allow second coat to dry at least 24 hours and burnish within 7 days of application. Longer dry time required in cooler temperatures and in higher humidity.

Clean Up & Storage

Wash tools with soap and water.

Properly dispose of all soiled rags and protect unused product from freezing.

To recycle or properly dispose of paint in your community call 1-800-CLEANUP (U.S.A. only) or visit www.Earth911.org.

LIMITED WARRANTY

Behr Process Corporation warrants that this product meets Behr's manufacturing specifications. If this product does not meet these specifications, Behr will, at its option and upon proof of purchase, either furnish an equivalent amount of new product to you or refund the purchase price of this product. **Behr will not be responsible for (1) labor or the cost of labor for removal or application of any product; or (2) any incidental or consequential damages, whether based on breach of express or implied warranty, negligence, strict liability or any other legal theory.** Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights and you may also have other rights, which vary from state to state.

Refer to the BEHR PREMIUM PLUS WITH STYLE® Faux Textures Colors & Techniques Guide for additional tips or visit us at www.behr.com for expert project advice and perfect color coordination with COLORSMART BY BEHR™.

To consult with a BEHR Certified Coatings Professional, call 1-800-854-0133 Ext. 2 (U.S.A. only).

©2008 BEHR PROCESS CORPORATION
Santa Ana, CA 92704 U.S.A.

†WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

WARNING! This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

WARNING! IRRITANT! HARMFUL IF SWALLOWED. CONTAINS: ETHYLENE GLYCOL. MAY CAUSE EYE, NOSE AND THROAT IRRITATION. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING OF VAPORS AND SPRAY MIST. WEAR EYE PROTECTION AND PROTECTIVE CLOTHING. USE ONLY WITH ADEQUATE VENTILATION. To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air. If properly used, a respirator (NIOSH approved for organic vapor with P series particulate pre-filter) may offer additional protection; obtain professional advice before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. FIRST AID: If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

CAUTION: KEEP OUT OF REACH OF CHILDREN – DO NOT TAKE INTERNALLY.





PREMIUM PLUS with STYLE® Venetian Plaster Topcoat No. 775

This 100% Acrylic, water-based, clear protective finish increases the durability and sheen of BEHR® Venetian Plaster.



Where To Use

As a clear protective topcoat to increase the durability of BEHR® VENETIAN PLASTER in high moisture and high traffic areas. Dries to a Satin sheen.

Preparation†

Apply after the VENETIAN PLASTER finish has completely dried, approximately 24 hours. Do not burnish the surface before or after the application of the VENETIAN PLASTER TOPCOAT.

Application

Refer to the BEHR Faux Textures Colors & Techniques Guide and www.behr.com for additional instructions on application. DO NOT THIN. Stir occasionally. Use product when the surface and air temperatures are between 50-90°F (10-32°C). Apply using a straight-edged, flexible steel trowel or wall scraper. Hold trowel at an angle, spreading a very thin, even coat of the product across the surface. Remove any excess topcoat with a damp rag or sponge. The topcoat will dry to a Satin sheen and darken the tone and/or color of the finish. Typical spread rate is 200 sq. ft. (19 m²) per quart.

Dry Time

Dries in 24 hours at 75°F (24°C) and 50% humidity. Additional dry time is needed in cooler temperatures and higher humidity.

After 2 weeks, the surface may be cleaned with a mild, non-abrasive liquid detergent.

Clean Up & Storage

Use soap and water.

Properly dispose of all soiled rags and protect unused product from freezing.

To recycle or properly dispose of paint in your community call 1-800-CLEANUP (U.S.A. only) or visit www.Earth911.org.

LIMITED WARRANTY

Behr Process Corporation warrants that this product meets Behr's manufacturing specifications. If this product does not meet these specifications, Behr will, at its option and upon proof of purchase, either furnish an equivalent amount of new product to you or refund the purchase price of this product. **Behr will not be responsible for (1) labor or the cost of labor for removal or application of any product; or (2) any incidental or consequential damages, whether based on breach of express or implied warranty, negligence, strict liability or any other legal theory.** Some states do not allow the exclusion or limitation of incidental or consequential damages, so

the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights and you may also have other rights, which vary from state to state.

Refer to the BEHR PREMIUM PLUS WITH STYLE® Faux Textures Colors & Techniques Guide for additional tips or visit us at www.behr.com for expert project advice and perfect color coordination with COLORSMART BY BEHR™.

To consult with a BEHR Certified Coatings Professional, call 1-800-854-0133 Ext. 2 (U.S.A. only).

©2008 BEHR PROCESS CORPORATION
Santa Ana, CA 92704 U.S.A.

†WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

WARNING! This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

WARNING! IRRITANT! HARMFUL IF SWALLOWED. CONTAINS: ETHYLENE GLYCOL. MAY CAUSE EYE, NOSE AND THROAT IRRITATION. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING OF VAPORS AND SPRAY MIST. WEAR EYE PROTECTION AND PROTECTIVE CLOTHING. USE ONLY WITH ADEQUATE VENTILATION. To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air. If properly used, a respirator (NIOSH approved for organic vapor with P series particulate pre-filter) may offer additional protection; obtain professional advice before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. FIRST AID: If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

CAUTION: KEEP OUT OF REACH OF CHILDREN - DO NOT TAKE INTERNALLY.





PREMIUM PLUS with STYLE® LUMINOSO™

This versatile, 100% Acrylic Interior water-based product provides the alluring look of metal. Available in a variety of colors, it allows you to give walls and objects an extraordinary finish that enhances and complements any style or decorative theme. Pre-mixed colors available in 14 Carat No. 741, Copper No. 742 and Silver No. 743 in select markets.



Where To Use

Properly painted or primed Interior surfaces. Ideal for Trim, Doors, Molding, Baseboards, Furniture, Picture Frames, Lamps, Architectural Accents and Decorative Metalwork. Can be applied to a wall over an existing base color using various techniques and tools as well as over a Faux Glazing technique using the same application technique.

Preparation†

Remove loose paint, wash off any dirt and grease with detergent, remove mildew stains with a product such as BEHR® MILDEW STAIN REMOVER NO. 62. Rinse and allow to dry.

Scuff sand glossy surfaces.

On metal surfaces, remove all rust with a wire brush.

Countersink nailheads, repair imperfections and sand smooth.

Remove all dust with a damp cloth, allow to dry.

Prime with a product such as BEHR ENAMEL UNDERCOATER PRIMER & SEALER NO. 75.

Application

Refer to the BEHR Faux Accents Colors & Techniques Guide and www.behr.com for additional instructions on application. Apply using a brush, roller, sea sponge, cloth rag or airless sprayer (.015 spray tip). Use product when the surface and air temperatures are between 50-90°F (10-32°C). Stir thoroughly before and occasionally during application. Do not thin if using a roller or brush. If using a sprayer and thinning is required, thin with water at a rate of no more than 2 oz. per quart. Typical coverage is 50 sq. ft. per quart. Two thin coats are necessary to achieve uniform coverage and hide.

Dry Time

Dries to touch in 1 hour at 75°F (24°C) and 50% humidity, re-coat in 4 hours.

Longer dry time required in cooler temperatures and in higher humidity.

After 4 weeks, surface is fully cured and may be cleaned with a mild, non-abrasive liquid detergent.

Clean Up & Storage

Wash tools with soap and water.

Properly dispose of all soiled rags and protect unused product from freezing.

To recycle or properly dispose of paint in your community call 1-800-CLEANUP (U.S.A. only) or visit www.Earth911.org.

LIMITED WARRANTY

Behr Process Corporation warrants that this product meets Behr's manufacturing specifications. If this product does not meet these specifications, Behr will, at its option and upon proof of purchase, either furnish an equivalent amount of new product to you or refund the purchase price of this product. **Behr will not be responsible for (1) labor or the cost of labor for removal or application of any product; or (2) any incidental or consequential damages, whether based on breach of express or implied warranty, negligence, strict liability or any other legal theory.** Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights and you may also have other rights, which vary from state to state.

Refer to the BEHR PREMIUM PLUS WITH STYLE® Faux Accents Colors & Techniques Guide for additional tips or visit us at www.behr.com for expert project advice and perfect color coordination with COLORSMART BY BEHR™.

To consult with a BEHR Certified Coatings Professional, call 1-800-854-0133 Ext. 2 (U.S.A. only).

©2008 BEHR PROCESS CORPORATION
Santa Ana, CA 92704 U.S.A.

†WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

WARNING! This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

WARNING! IRRITANT! HARMFUL IF SWALLOWED. CONTAINS: ETHYLENE GLYCOL. MAY CAUSE EYE, NOSE AND THROAT IRRITATION. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING OF VAPORS AND SPRAY MIST. WEAR EYE PROTECTION AND PROTECTIVE CLOTHING. USE ONLY WITH ADEQUATE VENTILATION. To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air. If properly used, a respirator (NIOSH approved for organic vapor with P series particulate pre-filter) may offer additional protection; obtain professional advice before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. FIRST AID: If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

CAUTION: KEEP OUT OF REACH OF CHILDREN - DO NOT TAKE INTERNALLY.





PREMIUM PLUS with STYLE® Pearlescent

This 100% Acrylic, water-based, translucent finish has a pearl-like feel that adds a soft sparkle or shimmer over a finished surface. It will add new dimension with a slight change in the surface color, enhancing decorative walls and accent finishes. Pre-mixed colors available in Gold Veil No. 750 and White Opal No. 751 in select markets.



Where To Use

Properly painted or primed Interior surfaces. Ideal for Trim, Doors, Molding, Baseboards, Furniture, Picture Frames, Lamps, Architectural Accents and Decorative Metalwork. Can be applied to a wall over an existing base color using various techniques and tools as well as over Faux Finishes using the same application technique.

Preparation†

Remove loose paint, wash off any dirt and grease with detergent, remove mildew stains with a product such as BEHR® MILDEW STAIN REMOVER NO. 62. Rinse and allow to dry.

On metal surfaces, remove all rust with a wire brush,

Prime with a product such as BEHR ENAMEL UNDERCOATER PRIMER & SEALER NO. 75.

Apply base color according to label instructions.

Application

Refer to the BEHR Faux Accents Colors & Techniques Guide and www.behr.com for additional instructions on application. Apply using a brush, roller, cloth rag or sea sponge. Use product when the surface and air temperatures are between 50-90°F (10-32°C). DO NOT THIN. Stir thoroughly before and occasionally during application. Typical coverage is 250-400 sq. ft. (23-37 m²) per quart.

Dry Time

Dries to touch in 1 hour at 75°F (24°C) and 50% humidity.

Longer dry time required in cooler temperatures and in higher humidity.

After 4 weeks, surface is fully cured and may be cleaned with a mild, non-abrasive liquid detergent.

Clean Up & Storage

Wash tools with soap and water.

Properly dispose of all soiled rags and protect unused product from freezing.

To recycle or properly dispose of paint in your community call 1-800-CLEANUP (U.S.A. only) or visit www.Earth911.org.

LIMITED WARRANTY

Behr Process Corporation warrants that this product meets Behr's manufacturing specifications. If this product does not meet these specifications, Behr will, at its option and upon proof of purchase, either furnish an equivalent amount of new product to you or refund the purchase price of this product. **Behr will not be responsible for (1)**

labor or the cost of labor for removal or application of any product; or (2) any incidental or consequential damages, whether based on breach of express or implied warranty, negligence, strict liability or any other legal theory. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights and you may also have other rights, which vary from state to state.

Refer to the BEHR PREMIUM PLUS WITH STYLE® Faux Accents Colors & Techniques Guide for additional tips or visit us at www.behr.com for expert project advice and perfect color coordination with COLORSMART BY BEHR™.

To consult with a BEHR Certified Coatings Professional, call 1-800-854-0133 Ext. 2 (U.S.A. only).

©2008 BEHR PROCESS CORPORATION
Santa Ana, CA 92704 U.S.A.

†WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

WARNING! This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

WARNING! IRRITANT! HARMFUL IF SWALLOWED. CONTAINS: ETHYLENE GLYCOL. MAY CAUSE EYE, NOSE AND THROAT IRRITATION. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING OF VAPORS AND SPRAY MIST. WEAR EYE PROTECTION AND PROTECTIVE CLOTHING. USE ONLY WITH ADEQUATE VENTILATION. To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air. If properly used, a respirator (NIOSH approved for organic vapor with P series particulate pre-filter) may offer additional protection; obtain professional advice before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. FIRST AID: If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

CAUTION: KEEP OUT OF REACH OF CHILDREN - DO NOT TAKE INTERNALLY.





PREMIUM PLUS with STYLE® Crackle No.755

This specially formulated, water-based product causes the top color to crack when applied between two layers of paint. It is designed to reproduce a random worn or aged finish with cracks and splits, revealing the base color.



Where To Use

Interior surfaces including Trim, Doors, Molding, Cabinets, Baseboards, Furniture, Windows, Picture Frames, Lamps, Curved or Rounded Objects and Decorative Metalwork. Not recommended for walls.

Preparation†

If using an existing latex base color, the surface must be clean and sound.

On metal surfaces, remove all rust with a wire brush.

If applying a new base color, use a product such as BEHR PREMIUM PLUS® Interior Flat, Flat Enamel, Eggshell Enamel or Satin Enamel following label instructions.

Allow to dry 4 hours. Additional time required in cooler temperatures and in higher humidity.

Application

Refer to the BEHR® Faux Accents Colors & Techniques Guide and www.behr.com for additional instructions on application.

Stir product occasionally. Once the base color is dry, apply a generous coat of BEHR CRACKLE using a nylon/polyester brush or high quality 1/4" synthetic nap roller.

When completely dry, approximately 1 hour, apply the desired BEHR PREMIUM PLUS Interior Flat Paint color. The top color will begin to crack as it dries, moments after it is applied.

Do not reapply over previously painted areas once the cracking begins.

After the top color has cured 24 hours, apply a product such as BEHR CRYSTAL CLEAR WATER-BASED POLYURETHANE NO. 780 for added durability and protection.

Use product when the surface and air temperatures are between 50-90°F (10-32°C). For best results, apply at 50% humidity or less. Typical coverage is 100-150 sq. ft. (9-14 m²) per quart on smooth sealed surfaces.

Dry Time

BEHR CRACKLE dries to be topcoated in approximately 1 hour at 75°F (24°C) and 50% humidity.

Allow top color to dry approximately 24 hours. Longer dry time required in cooler temperatures and higher humidity.

After 4 weeks, the surface is fully cured and may be carefully cleaned with a mild, non-abrasive liquid detergent.

Clean Up & Storage

Wash tools with soap and water.

Properly dispose of all soiled rags and protect unused product from freezing.

To recycle or properly dispose of paint in your community call 1-800-CLEANUP (U.S.A. only) or visit www.Earth911.org.

LIMITED WARRANTY

Behr Process Corporation warrants that this product meets Behr's manufacturing specifications. If this product does not meet these specifications, Behr will, at its option and upon proof of purchase, either furnish an equivalent amount of new product to you or refund the purchase price of this product. **Behr will not be responsible for (1) labor or the cost of labor for removal or application of any product; or (2) any incidental or consequential damages, whether based on breach of express or implied warranty, negligence, strict liability or any other legal theory.** Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights and you may also have other rights, which vary from state to state.

Refer to the BEHR PREMIUM PLUS WITH STYLE® Faux Accents Colors & Techniques Guide for additional tips or visit us at www.behr.com for expert project advice and perfect color coordination with COLORSMART BY BEHR™.

To consult with a BEHR Certified Coatings Professional, call 1-800-854-0133 Ext. 2 (U.S.A. only).

©2008 BEHR PROCESS CORPORATION
Santa Ana, CA 92704 U.S.A.

†WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

WARNING! This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

WARNING! IRRITANT! HARMFUL IF SWALLOWED. CONTAINS: ETHYLENE GLYCOL. MAY CAUSE EYE, NOSE AND THROAT IRRITATION. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING OF VAPORS AND SPRAY MIST. WEAR EYE PROTECTION AND PROTECTIVE CLOTHING. USE ONLY WITH ADEQUATE VENTILATION. To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air. If properly used, a respirator (NIOSH approved for organic vapor with P series particulate pre-filter) may offer additional protection; obtain professional advice before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. FIRST AID: If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

CAUTION: KEEP OUT OF REACH OF CHILDREN - DO NOT TAKE INTERNALLY.





PREMIUM PLUS with STYLE® Crystal Clear Water Based Polyurethane No.780



This ultra hard finish is ideal for use over interior painted, faux-finished, crackled and textured surfaces. It will enhance the look of the finish and protect it from moisture and wear. It dries to a durable, non-yellowing, clear, long-lasting matte finish.

Where To Use

Apply over interior painted, faux finished, crackled and textured surfaces to increase durability. Use over a product such as BEHR® SANDWASH wall finishes for added protection in high traffic and high moisture areas.

On interior smooth bare wood surfaces, water-based stained wood and craft projects.

Not for use over BEHR VENETIAN PLASTER. On these surfaces, use BEHR VENETIAN PLASTER TOPCOAT.

Preparation†

Allow surface being topcoated to dry completely according to label instructions.

Wipe all surfaces with a damp cloth to remove any dirt or dust.

On previously stained wood surfaces, where the surface topcoat is in good condition, thoroughly clean with a heavy duty industrial cleaner or wax remover. Allow to dry then sand with fine grit sandpaper. DO NOT USE STEEL WOOL. Wipe with a damp cloth.

Application

Wear appropriate respirator, eye and apparel protection.

Apply thin, even coats taking care not to puddle, overbrush or overlap finish. Always maintain a wet edge.

Apply using a nap roller no larger than 1/4" or a high-quality nylon/polyester brush or pad applicator at a spread rate of 300 to 400 sq. ft. per gallon. Do not use a natural bristle or foam brush, they will retain air and effect the finish. A sprayer will work well on large surfaces.

Allow three to four hours to dry thoroughly between coats.

Reseal original container immediately after use to reduce skinning or contamination of the product.

Do not thin. Product is formulated for use at package consistency only.

DO NOT SHAKE as shaking will generate air bubbles.

Stir thoroughly before and occasionally during application.

Use in a warm (50°F or higher), well-ventilated area.

Refer to the BEHR Techniques Guides and www.behr.com for additional instructions on application.

Dry Time

Dries to touch in one hour at 75°F (24°C) and 50% humidity. Re-coat in three to four hours.

Additional dry time is needed in cooler temperatures and higher humidity.

Three to four days after final coat, surface is fully cured and may be cleaned with a mild, non-abrasive liquid detergent.

Clean Up & Storage

Wash tools with soap and water.

Wipe excess product from lip of container with a clean cloth prior to sealing to avoid material gluing lid closed.

Dried spills must be cleaned with lacquer thinner or paint remover.

Properly dispose of all soiled rags and protect unused product from freezing.

To recycle or properly dispose of paint in your community call 1-800-CLEANUP (U.S.A. only) or visit www.Earth911.org.

LIMITED WARRANTY

Behr Process Corporation warrants that this product meets Behr's manufacturing specifications. If this product does not meet these specifications, Behr will, at its option and upon proof of purchase, either furnish an equivalent amount of new product to you or refund the purchase price of this product. **Behr will not be responsible for (1) labor or the cost of labor for removal or application of any product; or (2) any incidental or consequential damages, whether based on breach of express or implied warranty, negligence, strict liability or any other legal theory.** Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights and you may also have other rights, which vary from state to state.

Refer to the BEHR PREMIUM PLUS WITH STYLE® Faux Texture Colors & Techniques Guide for additional tips or visit us at www.behr.com for expert project advice and perfect color coordination with COLORSMART BY BEHR™.

To consult with a BEHR Certified Coatings Professional, call 1-800-854-0133 Ext. 2 (U.S.A. only).

©2008 BEHR PROCESS CORPORATION
Santa Ana, CA 92704 U.S.A.

†WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

WARNING! This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

WARNING! IRRITANT! HARMFUL IF SWALLOWED. CONTAINS: GLYCOL ETHERS. MAY CAUSE EYE, NOSE AND THROAT IRRITATION. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING OF VAPORS. WEAR EYE PROTECTION AND PROTECTIVE CLOTHING. USE WITH ADEQUATE VENTILATION. To avoid breathing vapors, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air. If properly used, a respirator (NIOSH approved for organic vapor with P series particulate pre-filter) may offer additional protection; obtain professional advice before using. Refer to respirator manufacturer's direction before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. FIRST AID: If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

CAUTION: KEEP OUT OF REACH OF CHILDREN - DO NOT TAKE INTERNALLY.

