



## Elastomeric Masonry, Stucco & Brick Paint

No. 68 White

- For Exterior Use
- 100% Acrylic Latex
- Stretches up to 600% to Resist Cracking
- Formulated with a Mildewcide
- Low Sheen

**IMPORTANT! DO NOT OPEN CAN WITHOUT READING INSTRUCTIONS.**

### WHERE TO USE

- Properly prepared exterior vertical surfaces such as: Stucco, Masonry, Concrete, Concrete Block or Brick as well as adjacent Wood and Metal surfaces.
- Not for use on horizontal surfaces subject to foot traffic.

### PREPARATION† (The following steps are recommended for best results.)

- Allow new stucco and masonry to cure for 30 days before painting.
- Remove all loose, peeling paint. Powerwash to remove chalk. Remove dirt and grease with BEHR® NO. 990 CONCRETE & MASONRY CLEANER/DEGREASER; remove mildew stains with BEHR NO. 62 PREMIUM MILDEW STAIN REMOVER. On galvanized metal, use a diluted solution of BEHR NO. 991 CONCRETE & MASONRY CLEANER/ETCHER to prepare surface. Follow all label instructions. Rinse thoroughly and allow a minimum of 24 hours to dry.
- Cracks and gaps wider than 1/16" (1.5 mm) should be routed open, dusted and patched with an elastomeric patching compound. Use an acrylic caulk around windows, doors and trim. Scuff sand glossy surfaces.
- Prime all uncoated, patched, chalky, wood and/or metal surfaces with BEHR NO. 436 EXTERIOR 100% ACRYLIC LATEX PRIMER & SEALER.

### APPLICATIONS

- DO NOT THIN. Intermix all cans of same product to ensure color uniformity. Stir paint before and occasionally during application.
- Use product when air and surface temperatures are between 50-90°F (10-32°C). Do not use if rain or heavy dew is expected within 24 hours.
- Apply using a high quality 1 1/4" nap roller, nylon/polyester brush or airless sprayer (.025-.029 spray tip). Spread rate is approximately

75-125 sq. ft. (7-12 m<sup>2</sup>) per gallon depending on type and porosity of surface. After 24 hours, a second coat **must** be applied at the same spread rate. A third coat may be required to achieve a final dry mil thickness of about 10-15 mils. If airless spraying, use equipment with a minimum of 2500 PSI at the tip.

- Maintain a wet edge to avoid lap marks. Do not re-spread or re-work paint.

### DRY TIME

- Dries to the touch in 4-6 hours. Longer dry time required in cooler temperatures and higher humidity. Allow 24 hours between coats. After two weeks, cured paint film may be cleaned with a mild, non-abrasive liquid detergent.

### CLEAN UP AND STORAGE

- Use soap and water. Properly dispose of all soiled rags and protect unused product from freezing. To recycle or properly dispose of paint in your community call 1-800-CLEANUP or visit [www.Earth911.org](http://www.Earth911.org).

† **WARNING!** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

**WARNING!** Sanding or scraping pressure treated lumber may be hazardous; wear appropriate protection.

**\*LIMITED LIFETIME GUARANTEE** BEHR PROCESS CORPORATION GUARANTEES THAT THIS PRODUCT WILL PROVIDE A WATERPROOF FINISH AND HIDE HAIRLINE CRACKS EXISTING AT TIME OF APPLICATION WHEN APPLIED AND CARED FOR ACCORDING TO LABEL DIRECTIONS. THIS GUARANTEE SHALL BE EFFECTIVE FOR SO LONG AS YOU RESIDE IN YOUR HOME AND IS MADE TO THE ORIGINAL RESIDENTIAL CONSUMER PAINT PURCHASER. THIS GUARANTEE IS NOT TRANSFERABLE. THIS GUARANTEE DOES NOT COVER WATER INTRUSION DUE TO STRUCTURAL DEFECTS OR CAULK FAILURE. Color fading and chalking will occur naturally over time. If this product fails to perform as specified, Behr Process Corporation will, at its option and upon proof-of-purchase, either furnish an equivalent amount of new paint to you, or refund the purchase price of this product. This guarantee excludes both (1) labor and costs of labor for the application or removal of any paint and (2) any incidental or consequential damages, whether based on breach of express or implied warranty, negligence, strict liability or any other legal theory. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This guarantee gives you specific legal rights and you may also have other rights, which vary from state to state.

To consult with a BEHR Certified Coatings Professional, call 1-800-854-0133 Ext. 2 (U.S.A. only).

**BEHR**  
A Masco Company

©2008 BEHR PROCESS CORPORATION  
Santa Ana, CA 92704 U.S.A. • [www.behr.com](http://www.behr.com)  
V.O.C. (C.O.V.) <100 g/L • REV. 2/08

**WARNING!** This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

**WARNING! IRRITANT! HARMFUL IF SWALLOWED. CONTAINS: ETHYLENE GLYCOL. MAY CAUSE EYE, NOSE AND THROAT IRRITATION. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING OF VAPORS AND SPRAY MIST. WEAR EYE PROTECTION AND PROTECTIVE CLOTHING. USE ONLY WITH ADEQUATE VENTILATION.** To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air. If properly used, a respirator (NIOSH approved for organic vapor with P series particulate pre-filter) may offer additional protection; obtain professional advice before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. **FIRST AID:** If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

**CAUTION: KEEP OUT OF REACH OF CHILDREN - DO NOT TAKE INTERNALLY.**



## Masonry, Stucco & Brick Paint - Flat

- Interior/Exterior Flat Finish
- Alkali Resistant Acrylic Latex
- Formulated with a Mildewcide
- Available In Custom Colors

No. 270 White

No. 271 Pastel Base

**IMPORTANT! DO NOT OPEN CAN WITHOUT READING INSTRUCTIONS.**  
FOR TINT BASES – DO NOT USE WITHOUT THE ADDITION OF TINTING COLORANTS

### WHERE TO USE

- Properly prepared Interior or Exterior vertical surfaces such as: Stucco, Masonry, Concrete, Concrete Block and Brick as well as adjacent Wood and Metal.
- Not for use on horizontal surfaces subject to foot traffic.

### PREPARATION† (The following steps are recommended for best results.)

- Allow new stucco and masonry to cure for 30 days before painting.
- Remove all loose, peeling paint. Powerwash to remove chalk. Remove dirt and grease with BEHR® NO. 990 CONCRETE & MASONRY CLEANER/DI-GREASER; remove mildew stains with BEHR NO. 62 PREMIUM MILDEW STAIN REMOVER. On galvanized metal, use a diluted solution of BEHR NO. 991 CONCRETE & MASONRY CLEANER/ETCHER to prepare the surface. Follow all label instructions. Rinse thoroughly and allow a minimum of 24 hours to dry.
- Cracks and gaps wider than 1/16" (1.5 mm) should be routed open, dusted and patched with a quality patching compound. Use an acrylic caulk around windows, doors and trim. Scuff sand glossy surfaces.
- If chalk remains on the surface, prime with a BEHR NO. 436 EXTERIOR 100% ACRYLIC LATEX PRIMER & SEALER. Prime all patched areas as well as adjacent wood and metal surfaces.
- If previously sealed or coated, check manufacturer's specifications before painting.

### APPLICATIONS

- DO NOT THIN. Intermix all cans of same product to ensure color uniformity. Stir paint before and occasionally during application.
- Use product when the air and surface temperatures are between 50-90°F (10-32°C). Do not use if rain or heavy dew is expected within 24 hours.
- Apply using a high quality 3/4-1" nap roller, nylon/polyester brush or airless sprayer (.015-.017 spray tip). Spread rate is approximately 250 to 300 sq. ft. (23-28 m<sup>2</sup>) per gallon on rough surfaces and up to 400 sq. ft. (37 m<sup>2</sup>) on smooth surfaces. Apply a second coat, if necessary.
- Maintain a wet edge to avoid lap marks. Do not re-spread or re-work paint.

**\*LIMITED WARRANTY** Behr Process Corporation warrants your satisfaction with this product for 20 years on vertical surfaces from date of purchase, when applied to a properly prepared surface in accordance with the label directions. Color fading and chalking will occur naturally over time. If you are not satisfied with this product, Behr will, at its option and upon proof of purchase, either furnish an equivalent amount of new product or refund the purchase price. This warranty is made to the original residential product purchaser and is not transferable. **Behr will not be responsible for (1) labor or the cost of labor for removal or application of any product or (2) any incidental or consequential damages, whether based upon breach of express or implied warranty, negligence, strict liability or any other legal theory.** Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights, and you may also have other rights, which vary from state to state.

To consult with a BEHR Certified Coatings Professional, call 1-800-854-0133 Ext. 2 (U.S.A. only).

**BEHR**  
A Masco Company

©2008 BEHR PROCESS CORPORATION  
Santa Ana, CA 92704 U.S.A. • www.behr.com  
V.O.C. (C.O.V.) <100 g/L • REV. 2/08

### DRY TIME

- Dries to the touch in 2-3 hours. Longer dry time required in cooler temperatures and higher humidity. Recoat in 4 hours, if necessary. After two weeks, cured paint film may be cleaned with a mild, non-abrasive liquid detergent.

### CLEAN UP AND STORAGE

- Use soap and water. Properly dispose of all soiled rags and protect unused product from freezing. To recycle or properly dispose of paint in your community call 1-800-CLEANUP or visit www.Earth911.org.

† **WARNING!** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

**WARNING!** Sanding or scraping pressure treated lumber may be hazardous; wear appropriate protection.

**WARNING!** This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

**WARNING! IRRITANT! HARMFUL IF SWALLOWED. CONTAINS: ETHYLENE GLYCOL. MAY CAUSE EYE, NOSE AND THROAT IRRITATION. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING OF VAPORS AND SPRAY MIST. WEAR EYE PROTECTION AND PROTECTIVE CLOTHING. USE ONLY WITH ADEQUATE VENTILATION.** To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air. If properly used, a respirator (NIOSH approved for organic vapor with P series particulate pre-filter) may offer additional protection; obtain professional advice before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. **FIRST AID:** If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

**CAUTION: KEEP OUT OF REACH OF CHILDREN - DO NOT TAKE INTERNALLY.**



## Masonry, Stucco & Brick Paint - Satin

- Interior/Exterior Satin Finish
- Alkali Resistant Acrylic Latex
- Formulated with a Mildewcide
- Available In Custom Colors

No. 280 White

No. 281 Pastel Base

**IMPORTANT! DO NOT OPEN CAN WITHOUT READING INSTRUCTIONS.**  
FOR TINT BASES – DO NOT USE WITHOUT THE ADDITION OF TINTING COLORANTS

### WHERE TO USE

- Properly prepared Interior or Exterior vertical surfaces such as: Stucco, Masonry, Concrete, Concrete Block and Brick as well as adjacent Wood and Metal.
- Not for use on horizontal surfaces subject to foot traffic.

### PREPARATION† (The following steps are recommended for best results.)

- Allow new stucco and masonry to cure for 30 days before painting.
- Remove all loose, peeling paint. Powerwash to remove chalk. Remove dirt and grease with BEHR® NO. 990 CONCRETE & MASONRY CLEANER/DEGREASER; remove mildew stains with BEHR NO. 62 PREMIUM MILDEW STAIN REMOVER. On galvanized metal, use a diluted solution of BEHR NO. 991 CONCRETE & MASONRY CLEANER/ETCHER to prepare the surface. Follow all label instructions. Rinse thoroughly and allow a minimum of 24 hours to dry.
- Cracks and gaps wider than 1/16" (1.5 mm) should be routed open, dusted and patched with a quality patching compound. Use an acrylic caulk around windows, doors and trim. Scuff sand glossy surfaces.
- If chalk remains on the surface, prime with a BEHR NO. 436 EXTERIOR 100% ACRYLIC LATEX PRIMER & SEALER. Prime all patched areas as well as adjacent wood and metal surfaces.
- If previously sealed or coated, check manufacturer's specifications before painting.

### APPLICATIONS

- DO NOT THIN. Intermix all cans of same product to ensure color uniformity. Stir paint before and occasionally during application.
- Use product when the air and surface temperatures are between 50-90°F (10-32°C). Do not use if rain or heavy dew is expected within 24 hours.
- Apply using a high quality 3/4-1" nap roller, nylon/polyester brush or airless sprayer (.015-.017 spray tip). Spread rate is approximately 250 to 300 sq. ft. (23-28 m<sup>2</sup>) per gallon on rough surfaces and up to 400 sq. ft. (37 m<sup>2</sup>) on smooth surfaces. Apply a second coat, if necessary.
- Maintain a wet edge to avoid lap marks. Do not re-spread or re-work paint.

**\*LIMITED WARRANTY** Behr Process Corporation warrants your satisfaction with this product for 20 years on vertical surfaces from date of purchase, when applied to a properly prepared surface in accordance with the label directions. Color fading and chalking will occur naturally over time. If you are not satisfied with this product, Behr will, at its option and upon proof of purchase, either furnish an equivalent amount of new product or refund the purchase price. This warranty is made to the original residential product purchaser and is not transferable. **Behr will not be responsible for (1) labor or the cost of labor for removal or application of any product or (2) any incidental or consequential damages, whether based upon breach of express or implied warranty, negligence, strict liability or any other legal theory.** Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights, and you may also have other rights, which vary from state to state.

To consult with a BEHR Certified Coatings Professional, call 1-800-854-0133 Ext. 2 (U.S.A. only).

**BEHR**  
A Masco Company

©2008 BEHR PROCESS CORPORATION  
Santa Ana, CA 92704 U.S.A. • www.behr.com  
V.O.C. (C.O.V.) <150 g/L • REV. 2/08

### DRY TIME

- Dries to the touch in 2-3 hours. Longer dry time required in cooler temperatures and higher humidity. Recoat in 4 hours, if necessary. After two weeks, cured paint film may be cleaned with a mild, non-abrasive liquid detergent.

### CLEAN UP AND STORAGE

- Use soap and water. Properly dispose of all soiled rags and protect unused product from freezing. To recycle or properly dispose of paint in your community call 1-800-CLEANUP or visit www.Earth911.org.

† **WARNING!** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

**WARNING!** Sanding or scraping pressure treated lumber may be hazardous; wear appropriate protection.

**WARNING!** This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

**WARNING! IRRITANT! HARMFUL IF SWALLOWED. CONTAINS: ETHYLENE GLYCOL. MAY CAUSE EYE, NOSE AND THROAT IRRITATION. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING OF VAPORS AND SPRAY MIST. WEAR EYE PROTECTION AND PROTECTIVE CLOTHING. USE ONLY WITH ADEQUATE VENTILATION.** To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air. If properly used, a respirator (NIOSH approved for organic vapor with P series particulate pre-filter) may offer additional protection; obtain professional advice before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. **FIRST AID:** If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

**CAUTION: KEEP OUT OF REACH OF CHILDREN - DO NOT TAKE INTERNALLY.**



## Barn & Fence Paint

- Durable Oil-Latex Formula
- Livestock-Safe Dry Finish
- Self Priming & Ready-to-Use
- Mildew Resistant Finish
- Easy Water Clean-Up

## No. 25 Barn Red

### **IMPORTANT! DO NOT OPEN CAN WITHOUT READING INSTRUCTIONS.**

#### **WHERE TO USE**

- Smooth or rough sawn Exterior vertical wood surfaces such as: Plywood, Fences, Shingles, Shakes, Siding, Laminates, and Masonry and Stucco surfaces.

#### **PREPARATION† (The following steps are recommended for best results.)**

- Remove mildew stains with BEHR® NO. 62 PREMIUM MILDEW STAIN REMOVER.

#### **Previously painted, stained or clear sealed wood:**

- Sand all glossy surfaces.
- If surface is in good condition, apply BARN & FENCE PAINT directly over clean, dry surface.
- If the latex or oil-based finish has started to crack, peel or flake, use BEHR NO. 64 PREMIUM STAIN & FINISH STRIPPER. Rinse thoroughly.
- Follow with BEHR NO. 63 PREMIUM 2-IN-1 WOOD PREP. Scrub, rinse, and allow to dry completely.

#### **New, weathered, pressure treated or uncoated wood:**

- Place cloth duct tape in random areas on the bare wood. Press the tape firmly then quickly remove it. If wood fibers or debris are pulled onto the tape, the wood surface is not sound and additional preparation is required as follows: Clean surface with BEHR NO. 64 PREMIUM STAIN & FINISH STRIPPER. Rinse. Follow with BEHR NO. 63 PREMIUM 2-IN-1 WOOD PREP at full strength to remove mill glaze and/or loose wood fibers, dirt and other debris. Rinse and allow to dry.

#### **APPLICATIONS**

- Do not use if temperature is below 50°F (10°C) or if rain is expected within 24 hours.
- Wood surfaces must be completely dry.
- When working with more than one container of the same color, intermix to ensure color uniformity.
- Redwood, Cedar, Cypress and other “bleeding” woods contain water soluble extractives which may cause discoloration of white and pastel colors; therefore prime the above type woods with one coat of BEHR NO. 436 EXTERIOR WATER-BASED ACRYLIC LATEX PRIMER SEALER to reduce these stains.
- Apply with a nylon/polyester brush at a spread rate of approximately

400 sq. ft. per gallon (37 m<sup>2</sup>) for the first coat on smooth surfaces, 500 sq. ft. (46 m<sup>2</sup>) per gallon on the second coat. On rough surfaces, 200 sq. ft. (19 m<sup>2</sup>) per gallon on the first coat and 250 sq. ft. (23 m<sup>2</sup>) per gallon on the second coat. On rough-sawn or textured wood apply with a 3/4” long nap roller or high quality airless sprayer. For airless spraying use a .015 tip.

- Keep a wet edge to reduce lapping and help control color uniformity.
- Always back-brush or back-roll during all application methods.
- Two coats may be necessary for complete hiding. Apply the second coat only after the first coat has thoroughly dried.

#### **DRY TIME**

- Dries to touch in 2-3 hours, 6-8 hours of drying needed before re-coating.

#### **CLEAN UP AND STORAGE**

- Brushes and other equipment may be immediately cleaned with soapy water.
- To recycle or properly dispose of paint in your community call 1-800-CLEANUP or visit [www.Earth911.org](http://www.Earth911.org).

† **WARNING!** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

**WARNING!** Sanding or scraping pressure treated lumber may be hazardous; wear appropriate protection.

**WARNING!** This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

**WARNING! IRRITANT! HARMFUL IF SWALLOWED. CONTAINS: ETHYLENE GLYCOL. MAY CAUSE EYE, NOSE AND THROAT IRRITATION. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING OF VAPORS AND SPRAY MIST. WEAR EYE PROTECTION AND PROTECTIVE CLOTHING. USE ONLY WITH ADEQUATE VENTILATION.** To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air. If properly used, a respirator (NIOSH approved for organic vapor with P series particulate pre-filter) may offer additional protection; obtain professional advice before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. **FIRST AID:** If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

**CAUTION: KEEP OUT OF REACH OF CHILDREN - DO NOT TAKE INTERNALLY.**

**LIMITED WARRANTY** BEHR PROCESS CORPORATION warrants that this product meets BEHR'S manufacturing specifications. If this product does not meet these specifications, BEHR will, at its option and upon proof of purchase, either furnish an equivalent amount of new product to you or refund the purchase price of this product. **BEHR will not be responsible for (1) labor or the cost of labor for removal or application of any product; or (2) any incidental or consequential damages, whether based on breach of express or implied warranty, negligence, strict liability or any other legal theory.** Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights and you may also have other rights, which vary from state to state.

To consult with a BEHR Certified Coatings Professional, call 1-800-854-0133 Ext. 2 (U.S.A. only).

**BEHR**  
A Masco Company

©2008 BEHR PROCESS CORPORATION  
Santa Ana, CA 92704 U.S.A. • [www.behr.com](http://www.behr.com)  
V.O.C. (C.O.V.) <100 g/L • REV. 2/08



## Barn & Fence Paint

- Durable Oil-Latex Formula
- Livestock-Safe Dry Finish
- Self Priming & Ready-to-Use
- Mildew Resistant Finish
- Easy Water Clean-Up

## No. 35 High-Hide White

### **IMPORTANT! DO NOT OPEN CAN WITHOUT READING INSTRUCTIONS.**

#### **WHERE TO USE**

- Smooth or rough sawn Exterior vertical wood surfaces such as: Plywood, Fences, Shingles, Shakes, Siding, Laminates, and Masonry and Stucco surfaces.

#### **PREPARATION† (The following steps are recommended for best results.)**

- Remove mildew stains with BEHR® NO. 62 PREMIUM MILDEW STAIN REMOVER.

#### **Previously painted, stained or clear sealed wood:**

- Sand all glossy surfaces.
- If surface is in good condition, apply BARN & FENCE PAINT directly over clean, dry surface.
- If the latex or oil-based finish has started to crack, peel or flake, use BEHR NO. 64 PREMIUM STAIN & FINISH STRIPPER. Rinse thoroughly.
- Follow with BEHR NO. 63 PREMIUM 2-IN-1 WOOD PREP. Scrub, rinse, and allow to dry completely.

#### **New, weathered, pressure treated or uncoated wood:**

- Place cloth duct tape in random areas on the bare wood. Press the tape firmly then quickly remove it. If wood fibers or debris are pulled onto the tape, the wood surface is not sound and additional preparation is required as follows: Clean surface with BEHR NO. 64 PREMIUM STAIN & FINISH STRIPPER. Rinse with BEHR NO. 63 PREMIUM 2-IN-1 WOOD PREP at full strength to remove mill glaze and/or loose wood fibers, dirt and other debris. Rinse and allow to dry.

#### **APPLICATIONS**

- Do not use if temperature is below 50°F (10°C) or if rain is expected within 24 hours.
- Wood surfaces must be completely dry.
- When working with more than one container of the same color, intermix to ensure color uniformity.
- Redwood, Cedar, Cypress and other “bleeding” woods contain water soluble extractives which may cause discoloration of white and pastel colors; therefore prime the above type woods with one coat of BEHR NO. 436 EXTERIOR WATER-BASED ACRYLIC LATEX PRIMER SEALER to reduce these stains.
- Apply with a nylon/polyester brush at a spread rate of approximately

400 sq. ft. per gallon (37 m<sup>2</sup>) for the first coat on smooth surfaces, 500 sq. ft. (46 m<sup>2</sup>) per gallon on the second coat. On rough surfaces, 200 sq. ft. (19 m<sup>2</sup>) per gallon on the first coat and 250 sq. ft. (23 m<sup>2</sup>) per gallon on the second coat. On rough-sawn or textured wood apply with a 3/4” long nap roller or high quality airless sprayer. For airless spraying use a .015 tip.

- Keep a wet edge to reduce lapping and help control color uniformity.
- Always back-brush or back-roll during all application methods.
- Two coats may be necessary for complete hiding. Apply the second coat only after the first coat has thoroughly dried.

#### **DRY TIME**

- Dries to touch in 2-3 hours, 6-8 hours of drying needed before re-coating.

#### **CLEAN UP AND STORAGE**

- Brushes and other equipment may be immediately cleaned with soapy water.
- To recycle or properly dispose of paint in your community call 1-800-CLEANUP or visit [www.Earth911.org](http://www.Earth911.org).

† **WARNING!** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

**WARNING!** Sanding or scraping pressure treated lumber may be hazardous; wear appropriate protection.

**WARNING!** This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

**WARNING! IRRITANT! HARMFUL IF SWALLOWED. CONTAINS: ETHYLENE GLYCOL. MAY CAUSE EYE, NOSE AND THROAT IRRITATION. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING OF VAPORS AND SPRAY MIST. WEAR EYE PROTECTION AND PROTECTIVE CLOTHING. USE ONLY WITH ADEQUATE VENTILATION.** To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air. If properly used, a respirator (NIOSH approved for organic vapor with P series particulate pre-filter) may offer additional protection; obtain professional advice before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. **FIRST AID:** If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

**CAUTION: KEEP OUT OF REACH OF CHILDREN - DO NOT TAKE INTERNALLY.**

**LIMITED WARRANTY** BEHR PROCESS CORPORATION warrants that this product meets BEHR'S manufacturing specifications. If this product does not meet these specifications, BEHR will, at its option and upon proof of purchase, either furnish an equivalent amount of new product to you or refund the purchase price of this product. **BEHR will not be responsible for (1) labor or the cost of labor for removal or application of any product; or (2) any incidental or consequential damages, whether based on breach of express or implied warranty, negligence, strict liability or any other legal theory.** Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights and you may also have other rights, which vary from state to state.

To consult with a BEHR Certified Coatings Professional, call 1-800-854-0133 Ext. 2 (U.S.A. only).

**BEHR**  
A Masco Company

©2008 BEHR PROCESS CORPORATION  
Santa Ana, CA 92704 U.S.A. • [www.behr.com](http://www.behr.com)  
V.O.C. (C.O.V.) <100 g/L • REV. 2/08



## Basement & Masonry Waterproofing Paint

No. 875 White

- Mildew Resistant Film
- Smooth, Decorative Flat Finish
- Withstands 98 mph Wind-Driven Rain
- 100% Styrene Acrylic
- Sprayable! Saves Application Time

### IMPORTANT! DO NOT OPEN CAN WITHOUT READING INSTRUCTIONS.

#### WHERE TO USE

- Walls subject to hydrostatic pressure. Ideal for above or below grade Basement Walls, Retaining Walls, Garage Walls, Masonry Walls, Cinder Blocks, Stucco, Brick, Foundations and Landscape Walls. Apply to dry or slightly damp surfaces. **Not for use on floors or walls with active water leaks.**

#### PREPARATION† (The following steps are recommended for best results.)

##### New or Unpainted Surfaces:

- New concrete must cure for a minimum of 30 days.
- Test for loose, flaking concrete by pressing a piece of masking or cellophane tape at various places, then pull it off with an abrupt action. If the tape does not pull the concrete from the surface, it can be painted. If the existing concrete is removed, the loose concrete should be removed down to a sound substrate.
- All holes or cracks must be properly patched with a fast setting hydraulic cement.
- Remove mildew stains with BEHR® NO. 62 PREMIUM MILDEW STAIN REMOVER. Follow all label instructions.
- All surfaces must be clean and free of dirt, dust, efflorescence and oil. Clean surface with BEHR NO. 991 CONCRETE & MASONRY CLEANER/ETCHER. Follow all label instructions.

##### Previously Painted Surfaces:

- BEHR NO. 875 BASEMENT & MASONRY WATERPROOFING PAINT provides best results when applied to bare or untreated surfaces. PREVIOUSLY PAINTED SURFACES IN GOOD, REPAINTABLE CONDITION MAY BE PAINTED WITH BEHR NO. 875, HOWEVER, BEHR WILL NOT GUARANTEE THE RESULTS.
- Test for loose, flaking paint by pressing a piece of masking or cellophane tape at various places, then pull it off with an abrupt action. If the tape does not pull the paint from the surface, it can be painted. If the existing paint is removed, the loose paint should be removed down to a sound substrate by wire brushing or sanding.
- For Interior or Exterior application; remove deteriorated coating prior to application. Follow all label instructions.
- Follow all preparation instructions under "New or Unpainted Surfaces" above.

**\*LIMITED WARRANTY** BEHR Process Corporation warrants customer satisfaction with this product for 10 years on vertical surfaces from date of purchase, when applied to a properly prepared uncoated surface in accordance with the label directions. Previously painted or treated surfaces are excluded from this warranty. Color fading and chalking will occur naturally over time. If you are not satisfied with this product, BEHR will, at its option and upon proof of purchase, either furnish an equivalent amount of new product or refund the purchase price. This warranty is made to the original residential product purchaser and is not transferable. **BEHR will not be responsible for (1) labor or the cost of labor for removal or application of any product or (2) any incidental or consequential damages, whether based upon breach of express or implied warranty, negligence, strict liability or any other legal theory.** Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights, and you may also have other rights, which vary from state to state.

To consult with a BEHR Certified Coatings Professional, call 1-800-854-0133 Ext. 2 (U.S.A. only).

**BEHR**  
A Masco Company

©2008 BEHR PROCESS CORPORATION  
Santa Ana, CA 92704 U.S.A. • www.behr.com  
V.O.C. (C.O.V.) <250 g/L • REV. 2/08

#### APPLICATIONS

- Stir well before use. Do not thin product. Use with adequate ventilation.
- Use product when the surface and air temperature are between 50-90°F (10-32°C).
- Apply to dry or slightly damp masonry walls. Wipe off any visible moisture with a dry cloth before painting.
- Apply using a high quality 1/2"-3/4" nap roller, 4" nylon/polyester brush or an airless sprayer @ 2,200-3,200 PSI using a .023-.025 spray tip.
- Apply at a spread rate of 75-100 sq. ft. (7-9 m<sup>2</sup>) per gallon on rough surfaces and 100-125 sq. ft. (9-12 m<sup>2</sup>) per gallon on smooth surfaces.
- Two coats minimum are required:

**First Coat:** Using a brush or roller, work the waterproofer onto the masonry wall surface making certain to cover any pores or voids.

**Second Coat:** Using a brush or roller, cover the entire surface. Properly fill any voids left after the first coat. Additional spot application may be needed depending on the porosity of the surface.

**Important: If leaking is still present after two coats, it indicates that voids or pinholes are still open. Re-apply product to these areas. DO NOT thin product or apply at a greater spread rate.**

#### DRY TIME

- Dries to touch in about one hour and can be recoated in four hours. Low temperatures or high humidity conditions will affect drying time. Full cure should be reached in 7-14 days.

#### CLEAN UP AND STORAGE

- Use soap and water. Properly dispose of all soiled rags and protect unused product from freezing. To recycle or properly dispose of paint in your community call 1-800-CLEANUP or visit www.Earth911.org.

† **WARNING!** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

**WARNING!** This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

**WARNING! IRRITANT! HARMFUL IF SWALLOWED. CONTAINS: ETHYLENE GLYCOL. MAY CAUSE EYE, NOSE AND THROAT IRRITATION. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING OF VAPORS AND SPRAY MIST. WEAR EYE PROTECTION AND PROTECTIVE CLOTHING. USE ONLY WITH ADEQUATE VENTILATION.** To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air. If properly used, a respirator (NIOSH approved for organic vapor with P series particulate pre-filter) may offer additional protection; obtain professional advice before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. **FIRST AID:** If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

**CAUTION: KEEP OUT OF REACH OF CHILDREN - DO NOT TAKE INTERNALLY.**



## Basement & Masonry Waterproofing Paint

No. 876 Basement Gray

- Mildew Resistant Film
- Smooth, Decorative Flat Finish
- Withstands 98 mph Wind-Driven Rain
- 100% Styrene Acrylic
- Sprayable! Saves Application Time

### IMPORTANT! DO NOT OPEN CAN WITHOUT READING INSTRUCTIONS.

#### WHERE TO USE

- Walls subject to hydrostatic pressure. Ideal for above or below grade Basement Walls, Retaining Walls, Garage Walls, Masonry Walls, Cinder Blocks, Stucco, Brick, Foundations and Landscape Walls. Apply to dry or slightly damp surfaces. **Not for use on floors or walls with active water leaks.**

#### PREPARATION† (The following steps are recommended for best results.)

##### New or Unpainted Surfaces:

- New concrete must cure for a minimum of 30 days.
- Test for loose, flaking concrete by pressing a piece of masking or cellophane tape at various places, then pull it off with an abrupt action. If the tape does not pull the concrete from the surface, it can be painted. If the existing concrete is removed, the loose concrete should be removed down to a sound substrate.
- All holes or cracks must be properly patched with a fast setting hydraulic cement.
- Remove mildew stains with BEHR® NO. 62 PREMIUM MILDEW STAIN REMOVER. Follow all label instructions.
- All surfaces must be clean and free of dirt, dust, efflorescence and oil. Clean surface with BEHR NO. 991 CONCRETE & MASONRY CLEANER/ETCHER. Follow all label instructions.

##### Previously Painted Surfaces:

- BEHR NO. 876 BASEMENT & MASONRY WATERPROOFING PAINT provides best results when applied to bare or untreated surfaces. PREVIOUSLY PAINTED SURFACES IN GOOD, REPAINTABLE CONDITION MAY BE PAINTED WITH BEHR NO. 876, HOWEVER, BEHR WILL NOT GUARANTEE THE RESULTS.
- Test for loose, flaking paint by pressing a piece of masking or cellophane tape at various places, then pull it off with an abrupt action. If the tape does not pull the paint from the surface, it can be painted. If the existing paint is removed, the loose paint should be removed down to a sound substrate by wire brushing or sanding.
- For Interior or Exterior application; remove deteriorated coating prior to application. Follow all label instructions.
- Follow all preparation instructions under "New or Unpainted Surfaces" above.

**\*LIMITED WARRANTY** BEHR Process Corporation warrants customer satisfaction with this product for 10 years on vertical surfaces from date of purchase, when applied to a properly prepared uncoated surface in accordance with the label directions. Previously painted or treated surfaces are excluded from this warranty. Color fading and chalking will occur naturally over time. If you are not satisfied with this product, BEHR will, at its option and upon proof of purchase, either furnish an equivalent amount of new product or refund the purchase price. This warranty is made to the original residential product purchaser and is not transferable. **BEHR will not be responsible for (1) labor or the cost of labor for removal or application of any product or (2) any incidental or consequential damages, whether based upon breach of express or implied warranty, negligence, strict liability or any other legal theory.** Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights, and you may also have other rights, which vary from state to state.

To consult with a BEHR Certified Coatings Professional, call 1-800-854-0133 Ext. 2 (U.S.A. only).

**BEHR**  
A Masco Company

©2008 BEHR PROCESS CORPORATION  
Santa Ana, CA 92704 U.S.A. • www.behr.com  
V.O.C. (C.O.V.) <250 g/L • REV. 2/08

#### APPLICATIONS

- Stir well before use. Do not thin product. Use with adequate ventilation.
- Use product when the surface and air temperature are between 50-90°F (10-32°C).
- Apply to dry or slightly damp masonry walls. Wipe off any visible moisture with a dry cloth before painting.
- Apply using a high quality 1/2"-3/4" nap roller, 4" nylon/polyester brush or an airless sprayer @ 2,200-3,200 PSI using a .023-.025 spray tip.
- Apply at a spread rate of 75-100 sq. ft. (7-9 m<sup>2</sup>) per gallon on rough surfaces and 100-125 sq. ft. (9-12 m<sup>2</sup>) per gallon on smooth surfaces.
- Two coats minimum are required:

**First Coat:** Using a brush or roller, work the waterproofer onto the masonry wall surface making certain to cover any pores or voids.

**Second Coat:** Using a brush or roller, cover the entire surface. Properly fill any voids left after the first coat. Additional spot application may be needed depending on the porosity of the surface.

**Important: If leaking is still present after two coats, it indicates that voids or pinholes are still open. Re-apply product to these areas. DO NOT thin product or apply at a greater spread rate.**

#### DRY TIME

- Dries to touch in about one hour and can be recoated in four hours. Low temperatures or high humidity conditions will affect drying time. Full cure should be reached in 7-14 days.

#### CLEAN UP AND STORAGE

- Use soap and water. Properly dispose of all soiled rags and protect unused product from freezing. To recycle or properly dispose of paint in your community call 1-800-CLEANUP or visit www.Earth911.org.

† **WARNING!** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

**WARNING!** This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

**WARNING! IRRITANT! HARMFUL IF SWALLOWED. CONTAINS: ETHYLENE GLYCOL. MAY CAUSE EYE, NOSE AND THROAT IRRITATION. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING OF VAPORS AND SPRAY MIST. WEAR EYE PROTECTION AND PROTECTIVE CLOTHING. USE ONLY WITH ADEQUATE VENTILATION.** To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air. If properly used, a respirator (NIOSH approved for organic vapor with P series particulate pre-filter) may offer additional protection; obtain professional advice before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. **FIRST AID:** If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

**CAUTION: KEEP OUT OF REACH OF CHILDREN - DO NOT TAKE INTERNALLY.**



## Concrete & Masonry Waterproofing Paint

No. 870 White

- Mildew Resistant Film
- Smooth, Decorative Flat Finish
- Withstands 98 mph Wind-Driven Rain
- 100% Styrene Acrylic
- Sprayable! Saves Application Time

### IMPORTANT! DO NOT OPEN CAN WITHOUT READING INSTRUCTIONS.

#### WHERE TO USE

- Walls subject to hydrostatic pressure. Ideal for above or below grade Basement Walls, Retaining Walls, Garage Walls, Masonry Walls, Cinder Blocks, Stucco, Brick, Foundations and Landscape Walls. Apply to dry or slightly damp surfaces. **Not for use on floors or walls with active water leaks.**

#### PREPARATION† (The following steps are recommended for best results.)

##### New or Unpainted Surfaces:

- New concrete must cure for a minimum of 30 days.
- Test for loose, flaking concrete by pressing a piece of masking or cellophane tape at various places, then pull it off with an abrupt action. If the tape does not pull the concrete from the surface, it can be painted. If the existing concrete is removed, the loose concrete should be removed down to a sound substrate.
- All holes or cracks must be properly patched with a fast setting hydraulic cement.
- Remove mildew stains with BEHR® NO. 62 PREMIUM MILDEW STAIN REMOVER. Follow all label instructions.
- All surfaces must be clean and free of dirt, dust, efflorescence and oil. Clean surface with BEHR NO. 991 CONCRETE & MASONRY CLEANER/ETCHER. Follow all label instructions.

##### Previously Painted Surfaces:

- BEHR NO. 870 CONCRETE & MASONRY WATERPROOFING PAINT provides best results when applied to bare or untreated surfaces. PREVIOUSLY PAINTED SURFACES IN GOOD, REPAINTABLE CONDITION MAY BE PAINTED WITH BEHR NO. 870, HOWEVER, BEHR WILL NOT GUARANTEE THE RESULTS.
- Test for loose, flaking paint by pressing a piece of masking or cellophane tape at various places, then pull it off with an abrupt action. If the tape does not pull the paint from the surface, it can be painted. If the existing paint is removed, the loose paint should be removed down to a sound substrate by wire brushing or sanding.
- For Interior or Exterior application; remove deteriorated coating prior to application. Follow all label instructions.
- Follow all preparation instructions under "New or Unpainted Surfaces" above.

**\*LIMITED WARRANTY** BEHR PROCESS CORPORATION warrants customer satisfaction with this product for 10 years on vertical surfaces from date of purchase, when applied to a properly prepared uncoated surface in accordance with the label directions. Previously painted or treated surfaces are excluded from this warranty. Color fading and chalking will occur naturally over time. If you are not satisfied with this product, BEHR will, at its option and upon proof of purchase, either furnish an equivalent amount of new product or refund the purchase price. This warranty is made to the original residential product purchaser and is not transferable. **BEHR will not be responsible for (1) labor or the cost of labor for removal or application of any product or (2) any incidental or consequential damages, whether based upon breach of express or implied warranty, negligence, strict liability or any other legal theory.** Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights, and you may also have other rights, which vary from state to state.

To consult with a BEHR Certified Coatings Professional, call 1-800-854-0133 Ext. 2 (U.S.A. only).

**BEHR**  
A Masco Company

©2008 BEHR PROCESS CORPORATION  
Santa Ana, CA 92704 U.S.A. • www.behr.com  
V.O.C. (C.O.V.) <250 g/L • REV. 2/08

#### APPLICATIONS

- Stir well before use. Do not thin product. Use with adequate ventilation.
- Use product when the surface and air temperature are between 50-90°F (10-32°C).
- Apply to dry or slightly damp masonry walls. Wipe off any visible moisture with a dry cloth before painting.
- Apply using a high quality 1/2"-3/4" nap roller, 4" nylon/polyester brush or an airless sprayer @ 2,200-3,200 PSI using a .023-.025 spray tip.
- Apply at a spread rate of 75-100 sq. ft. (7-9 m<sup>2</sup>) per gallon on rough surfaces and 100-125 sq. ft. (9-12 m<sup>2</sup>) per gallon on smooth surfaces.
- Two coats minimum are required:

**First Coat:** Using a brush or roller, work the waterproofer onto the masonry wall surface making certain to cover any pores or voids.

**Second Coat:** Using a brush or roller, cover the entire surface. Properly fill any voids left after the first coat. Additional spot application may be needed depending on the porosity of the surface.

**Important: If leaking is still present after two coats, it indicates that voids or pinholes are still open. Re-apply product to these areas. DO NOT thin product or apply at a greater spread rate.**

#### DRY TIME

- Dries to touch in about one hour and can be recoated in four hours. Low temperatures or high humidity conditions will affect drying time. Full cure should be reached in 7-14 days.

#### CLEAN UP AND STORAGE

- Use soap and water. Properly dispose of all soiled rags and protect unused product from freezing. To recycle or properly dispose of paint in your community call 1-800-CLEANUP or visit www.Earth911.org.

† **WARNING!** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

**WARNING!** This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

**WARNING! IRRITANT! HARMFUL IF SWALLOWED. CONTAINS: ETHYLENE GLYCOL. MAY CAUSE EYE, NOSE AND THROAT IRRITATION. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING OF VAPORS AND SPRAY MIST. WEAR EYE PROTECTION AND PROTECTIVE CLOTHING. USE ONLY WITH ADEQUATE VENTILATION.** To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air. If properly used, a respirator (NIOSH approved for organic vapor with P series particulate pre-filter) may offer additional protection; obtain professional advice before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. **FIRST AID:** If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

**CAUTION: KEEP OUT OF REACH OF CHILDREN - DO NOT TAKE INTERNALLY.**





## Oil-Base High-Gloss Enamel

- Excellent Flow & Leveling
- Fast Dry Time
- Easy Stain Removal
- Mildew Resistant Finish

No. 8800 White

No. 8830 Deep Base

No. 8850 Pastel Base

No. 8860 Accent Base

### IMPORTANT! DO NOT OPEN CAN WITHOUT READING INSTRUCTIONS.

#### WHERE TO USE

- Properly prepared Interior or Exterior surfaces such as: Wood, Drywall, Plaster, Masonry, Metal, Well-bonded Wallpaper, Brick, Stucco, Aluminum and Cinder Block. Do not use on horizontal surfaces.

#### PREPARATION† (The following steps are recommended for best results.)

- Allow new stucco, plaster and masonry to cure for 30 days.
- **CLEAN:** For interior and exterior surfaces, remove dirt, oil and grease stains with BEHR® NO. 990 CONCRETE & MASONRY CLEANER/DEGREASER. To remove mildew stains, use BEHR NO. 62 PREMIUM MILDEW STAIN REMOVER. Remove all loose and peeling paint; scuff sand glossy surfaces; caulk; repair imperfections and sand smooth. For exterior surfaces, powerwash to remove chalk. Etch galvanized metal with BEHR NO. 991 CONCRETE & MASONRY CLEANER/ETCHER. Follow all label instructions.
- **PRIME:** Use BEHR NO. 436 100% ACRYLIC PRIMER & SEALER or BEHR NO. 434 OIL-BASED PRIMER & SEALER. Follow all label instructions.

#### APPLICATIONS

- DO NOT THIN. Stir before and during application. When working with more than one can of the same product, intermix to ensure color uniformity. Use adequate ventilation during application & drying process. Certain colors may require more than one coat to achieve complete hide and coverage. Use product when air and surface temperatures are between 40–90°F (4–32°C).
- Apply a thin coat using a high quality china bristle brush, 1/4-3/8" nap roller or an airless sprayer (0.013-0.015 spray tip) at a spread rate of 500-550 sq. ft. (46-51 m<sup>2</sup>) per gallon over primed smooth surfaces and 350-400 sq. ft. (33-37 m<sup>2</sup>) per gallon over primed rough surfaces.

#### DRY TIME

- Dries to the touch in 4-5 hours. Longer dry time required in cooler temperatures and higher humidity. Recoat in 24 hours. Wait at least 7 days before rinsing or cleaning the surface with a mild, non-abrasive detergent.

**LIMITED WARRANTY** BEHR PROCESS CORPORATION warrants that this product meets BEHR's manufacturing specifications. If this product does not meet these specifications, BEHR will, at its option and upon proof-of-purchase, either furnish an equivalent amount of new product to you or refund the purchase price of this product. **In no event will BEHR be responsible for (1) labor or the cost of labor for removal or application of any product; or (2) any incidental or consequential damages, whether based on breach of express or implied warranty, negligence, strict liability or any other legal theory.** Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights and you may also have other rights, which vary from state to state.

To consult with a BEHR Certified Coatings Professional, call 1-800-854-0133 Ext. 2 (U.S.A. only).

**BEHR**  
A Masco Company

©2008 BEHR PROCESS CORPORATION  
Santa Ana, CA 92704 U.S.A. • www.behr.com  
V.O.C. (C.O.V.) <380 g/L • REV. 2/08

#### CLEAN UP AND STORAGE

- Use mineral spirits. Properly dispose of all soiled rags and protect unused product from freezing. To recycle or properly dispose of paint in your community call 1-800-CLEANUP (U.S.A. only) or visit [www.Earth911.org](http://www.Earth911.org).

† **WARNING!** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

**WARNING!** Sanding or scraping pressure treated lumber may be hazardous; wear appropriate protection.



**IMPORTANT! STORAGE AND DISPOSAL: DANGER!** Rags, steel wool and waste soaked with this BEHR OIL-BASE HIGH-GLOSS ENAMEL may spontaneously catch fire if improperly discarded or stored. To avoid a spontaneous combustion fire, immediately after use, place rags, steel wool or waste in a sealed, water-filled, metal container. Do not store unused product inside the home. For disposal guidance, contact your household refuse collection service, fire department, county or state government environmental control agency.

**WARNING!** This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

**DANGER! COMBUSTIBLE LIQUID AND VAPOR. CONTAINS PETROLEUM DISTILLATES AND ALKYD RESIN. VAPOR HARMFUL. MAY AFFECT THE BRAIN OR NERVOUS SYSTEM CAUSING DIZZINESS, HEADACHE OR NAUSEA. CAUSES EYE, SKIN, NOSE AND THROAT IRRITATION.**

**NOTICE:** Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain or nervous system damage. Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. Keep away from heat and flame. Do not smoke. Close container after each use. **USE ONLY WITH ADEQUATE VENTILATION.** To avoid breathing vapors or spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. Do not use in an unventilated area. If properly used, a respirator (NIOSH approved for organic vapor with P series particulate pre-filter) may offer additional protection; obtain professional advice before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. **FIRST AID:** If swallowed, do not induce vomiting. Call a physician immediately. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water.

**CAUTION: KEEP OUT OF REACH OF CHILDREN - DO NOT TAKE INTERNALLY.**



## Oil-Base Semi-Gloss Enamel

- Excellent Flow & Leveling
- Fast Dry Time
- Easy Stain Removal
- Mildew Resistant Finish

No. 3800 White

No. 3812 Swiss Coffee

No. 3830 Deep Base

No. 3850 Pastel Base

No. 3860 Accent Base

### IMPORTANT! DO NOT OPEN CAN WITHOUT READING INSTRUCTIONS.

#### WHERE TO USE

- Properly prepared Interior or Exterior surfaces such as: Wood, Drywall, Plaster, Masonry, Metal, Well-bonded Wallpaper, Brick, Stucco, Aluminum and Cinder Block. Do not use on horizontal surfaces.

#### PREPARATION† (The following steps are recommended for best results.)

- Allow new stucco, plaster and masonry to cure for 30 days.
- **CLEAN:** For interior and exterior surfaces, remove dirt, oil and grease stains with BEHR® NO. 990 CONCRETE & MASONRY CLEANER/DEGREASER. To remove mildew stains, use BEHR NO. 62 PREMIUM MILDEW STAIN REMOVER. Remove all loose and peeling paint; scuff sand glossy surfaces; caulk; repair imperfections and sand smooth. For exterior surfaces, powerwash to remove chalk. Etch galvanized metal with BEHR NO. 991 CONCRETE & MASONRY CLEANER/ETCHER. Follow all label instructions.
- **PRIME:** Use BEHR NO. 436 100% ACRYLIC PRIMER & SEALER or BEHR NO. 434 OIL-BASED PRIMER & SEALER. Follow all label instructions.

#### APPLICATIONS

- DO NOT THIN. Stir before and during application. When working with more than one can of the same product, intermix to ensure color uniformity. Use adequate ventilation during application & drying process. Certain colors may require more than one coat to achieve complete hide and coverage. Use product when air and surface temperatures are between 40–90°F (4–32°C).
- Apply a thin coat using a high quality china bristle brush, 1/4-3/8" nap roller or an airless sprayer (0.013-0.015 spray tip) at a spread rate of 500-550 sq. ft. (46-51 m<sup>2</sup>) per gallon over primed smooth surfaces and 350-400 sq. ft. (33-37 m<sup>2</sup>) per gallon over primed rough surfaces.

#### DRY TIME

- Dries to the touch in 4-5 hours. Longer dry time required in cooler temperatures and higher humidity. Recoat in 24 hours. Wait at least 7 days before rinsing or cleaning the surface with a mild, non-abrasive detergent.

**LIMITED WARRANTY** BEHR PROCESS CORPORATION warrants that this product meets BEHR's manufacturing specifications. If this product does not meet these specifications, BEHR will, at its option and upon proof-of-purchase, either furnish an equivalent amount of new product to you or refund the purchase price of this product. **In no event will BEHR be responsible for (1) labor or the cost of labor for removal or application of any product; or (2) any incidental or consequential damages, whether based on breach of express or implied warranty, negligence, strict liability or any other legal theory.** Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights and you may also have other rights, which vary from state to state.

To consult with a BEHR Certified Coatings Professional, call 1-800-854-0133 Ext. 2 (U.S.A. only).

**BEHR**  
A Masco Company

©2008 BEHR PROCESS CORPORATION  
Santa Ana, CA 92704 U.S.A. • www.behr.com  
V.O.C. (C.O.V.) <380 g/L • REV. 2/08

#### CLEAN UP AND STORAGE

- Use mineral spirits. Properly dispose of all soiled rags and protect unused product from freezing. To recycle or properly dispose of paint in your community call 1-800-CLEANUP (U.S.A. only) or visit [www.Earth911.org](http://www.Earth911.org).

† **WARNING!** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

**WARNING!** Sanding or scraping pressure treated lumber may be hazardous; wear appropriate protection.



**IMPORTANT! STORAGE AND DISPOSAL: DANGER!** Rags, steel wool and waste soaked with this BEHR OIL-BASE SEMI-GLOSS ENAMEL may spontaneously catch fire if improperly discarded or stored. To avoid a spontaneous combustion fire, immediately after use, place rags, steel wool or waste in a sealed, water-filled, metal container. Do not store unused product inside the home. For disposal guidance, contact your household refuse collection service, fire department, county or state government environmental control agency.

**WARNING!** This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

**DANGER! COMBUSTIBLE LIQUID AND VAPOR. CONTAINS PETROLEUM DISTILLATES AND ALKYD RESIN. VAPOR HARMFUL. MAY AFFECT THE BRAIN OR NERVOUS SYSTEM CAUSING DIZZINESS, HEADACHE OR NAUSEA. CAUSES EYE, SKIN, NOSE AND THROAT IRRITATION.**

**NOTICE:** Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain or nervous system damage. Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. Keep away from heat and flame. Do not smoke. Close container after each use. **USE ONLY WITH ADEQUATE VENTILATION.** To avoid breathing vapors or spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. Do not use in an unventilated area. If properly used, a respirator (NIOSH approved for organic vapor with P series particulate pre-filter) may offer additional protection; obtain professional advice before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. **FIRST AID:** If swallowed, do not induce vomiting. Call a physician immediately. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water.

**CAUTION: KEEP OUT OF REACH OF CHILDREN - DO NOT TAKE INTERNALLY.**



## Flat Finish Roof Paint

## No. 65 White Reflective

- 100% Acrylic Latex for Excellent Adhesion
- Resists Fading
- Non-Yellowing
- For Tile, Aluminum, Metal, Wood or Asphalt Shingles

### IMPORTANT! DO NOT OPEN CAN WITHOUT READING INSTRUCTIONS.

#### WHERE TO USE

- New or old Unglazed Tile, Masonry Shingle, Anchored Gravel, Aluminum/Metal Materials, Composition Sheet, Asphalt Shingle, Concrete or Cement Block, Urethane Foam, Slate or Wood Shake Roofs. It is NOT intended to waterproof or repair roof leaks.
- This product is intended to brighten roofs and reflect heat.

**CAUTION:** Roof surfaces may become extremely slippery when wet. Avoid walking on surface while moisture is present. This product is not a fire retardant.

#### PREPARATION† (The following steps are recommended for best results.)

- Replace brittle or cracked shingles.
- Clean all roof surfaces. Previously coated surfaces should be wire brushed or scraped to remove all loose coating. Remove mildew with BEHR® NO. 62 PREMIUM MILDEW STAIN REMOVER. On galvanized metal, use a diluted solution of BEHR NO. 991 CONCRETE & MASONRY CLEANER/ETCHER to prepare surface. If applying on wood shakes, clean with BEHR NO. 63 PREMIUM 2-IN-1 WOOD PREP. Follow directions on product labels. Rinse thoroughly and allow a minimum of 24 hours to dry.
- Prime all metal, asphalt and wood surfaces with BEHR NO. 436 EXTERIOR 100% ACRYLIC LATEX PRIMER & SEALER. Follow directions on product label.

#### APPLICATIONS

- DO NOT THIN. When working with more than one can of the same product, inter-mix to ensure color uniformity. Stir paint before and occasionally during application.
- Use product when the air and surface temperatures are between 50-90°F (10-32°C). Do not use if rain or heavy dew is expected within 24 hours. Do not apply in direct sunlight. All roof surfaces must be dry.
- Apply starting at the top of the roof and working down, using a high quality 1" nap roller, nylon/polyester brush or high quality airless sprayer (.015-.017 sprayer tip).
- For rough textured surfaces, apply at a spread rate of approximately 250 sq. ft. (23 m<sup>2</sup>) per gallon. Apply a second coat at a spread rate of about 350 sq. ft. (32 m<sup>2</sup>) per gallon. For smooth surfaces, apply at a spread rate of about 350 sq. ft. (32 m<sup>2</sup>) per gallon. Apply a second coat at a spread rate of about 450 sq. ft. (42 m<sup>2</sup>) per gallon.
- Recoat in 4 hours. Always maintain a wet edge to avoid lap marks.

**LIMITED WARRANTY** BEHR PROCESS CORPORATION warrants that this product meets BEHR'S manufacturing specifications. If this product does not meet these specifications, BEHR will, at its option and upon proof of purchase, either furnish an equivalent amount of new product to you or refund the purchase price of this product. **BEHR will not be responsible for (1) labor or the cost of labor for removal or application of any product; or (2) any incidental or consequential damages, whether based on breach of express or implied warranty, negligence, strict liability or any other legal theory.** Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights and you may also have other rights, which vary from state to state.

To consult with a BEHR Certified Coatings Professional, call 1-800-854-0133 Ext. 2 (U.S.A. only).



A Masco Company

©2008 BEHR PROCESS CORPORATION  
Santa Ana, CA 92704 U.S.A. • www.behr.com  
V.O.C. (C.O.V.) <50 g/L • REV. 2/08

#### DRY TIME

- Dries to the touch in approximately 2 hours. Longer dry time required in cooler temperatures and higher humidity.

#### CLEAN UP AND STORAGE

- Use soap and water. Properly dispose of all soiled rags and protect unused product from freezing.
- To recycle or properly dispose of paint in your community call 1-800-CLEANUP or visit [www.Earth911.org](http://www.Earth911.org).

† **WARNING!** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

**WARNING!** Sanding or scraping pressure treated lumber may be hazardous; wear appropriate protection.

**WARNING!** This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

**WARNING! IRRITANT! HARMFUL IF SWALLOWED. CONTAINS: ETHYLENE GLYCOL. MAY CAUSE EYE, NOSE AND THROAT IRRITATION. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING OF VAPORS AND SPRAY MIST. WEAR EYE PROTECTION AND PROTECTIVE CLOTHING. USE ONLY WITH ADEQUATE VENTILATION.** To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air. If properly used, a respirator (NIOSH approved for organic vapor with P series particulate pre-filter) may offer additional protection; obtain professional advice before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. **FIRST AID:** If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

**CAUTION: KEEP OUT OF REACH OF CHILDREN - DO NOT TAKE INTERNALLY.**



## Flat Finish Roof Paint

## No. 66 Deep Base

- 100% Acrylic Latex for Excellent Adhesion
- Resists Fading
- Non-Yellowing
- For Tile, Aluminum, Metal, Wood or Asphalt Shingles

**IMPORTANT! DO NOT OPEN CAN WITHOUT READING INSTRUCTIONS.**  
FOR TINT BASES – DO NOT USE WITHOUT THE ADDITION OF TINTING COLORANTS

### WHERE TO USE

- New or old Unglazed Tile, Masonry Shingle, Anchored Gravel, Aluminum/Metal Materials, Composition Sheet, Asphalt Shingle, Concrete or Cement Block, Urethane Foam, Slate or Wood Shake Roofs. It is NOT intended to waterproof or repair roof leaks.
- This product is intended to brighten roofs and reflect heat.

**CAUTION:** Roof surfaces may become extremely slippery when wet. Avoid walking on surface while moisture is present. This product is not a fire retardant.

### PREPARATION† (The following steps are recommended for best results.)

- Replace brittle or cracked shingles.
- Clean all roof surfaces. Previously coated surfaces should be wire brushed or scraped to remove all loose coating. Remove mildew with BEHR® NO. 62 PREMIUM MILDEW STAIN REMOVER. On galvanized metal, use a diluted solution of BEHR NO. 991 CONCRETE & MASONRY CLEANER/ETCHER to prepare surface. If applying on wood shakes, clean with BEHR NO. 63 PREMIUM 2-IN-1 WOOD PREP. Follow directions on product labels. Rinse thoroughly and allow a minimum of 24 hours to dry.
- Prime all metal, asphalt and wood surfaces with BEHR NO. 436 EXTERIOR 100% ACRYLIC LATEX PRIMER & SEALER. Follow directions on product label.

### APPLICATIONS

- DO NOT THIN. When working with more than one can of the same product, inter-mix to ensure color uniformity. Stir paint before and occasionally during application.
- Use product when the air and surface temperatures are between 50-90°F (10-32°C). Do not use if rain or heavy dew is expected within 24 hours. Do not apply in direct sunlight. All roof surfaces must be dry.
- Apply starting at the top of the roof and working down, using a high quality 1" nap roller, nylon/polyester brush or high quality airless sprayer (.015-.017 sprayer tip).
- For rough textured surfaces, apply at a spread rate of approximately 250 sq. ft. (23 m<sup>2</sup>) per gallon. Apply a second coat at a spread rate of about 350 sq. ft. (32 m<sup>2</sup>) per gallon. For smooth surfaces, apply at a spread rate of about 350 sq. ft. (32 m<sup>2</sup>) per gallon. Apply a second coat at a spread rate of about 450 sq. ft. (42 m<sup>2</sup>) per gallon.

**LIMITED WARRANTY** BEHR PROCESS CORPORATION warrants that this product meets BEHR'S manufacturing specifications. If this product does not meet these specifications, BEHR will, at its option and upon proof of purchase, either furnish an equivalent amount of new product to you or refund the purchase price of this product. **BEHR will not be responsible for (1) labor or the cost of labor for removal or application of any product; or (2) any incidental or consequential damages, whether based on breach of express or implied warranty, negligence, strict liability or any other legal theory.** Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights and you may also have other rights, which vary from state to state.

To consult with a BEHR Certified Coatings Professional, call 1-800-854-0133 Ext. 2 (U.S.A. only).

**BEHR**  
A Masco Company

©2008 BEHR PROCESS CORPORATION  
Santa Ana, CA 92704 U.S.A. • www.behr.com  
V.O.C. (C.O.V.) <50 g/L • REV. 2/08

- Recoat in 4 hours. Always maintain a wet edge to avoid lap marks.

### DRY TIME

- Dries to the touch in approximately 2 hours. Longer dry time required in cooler temperatures and higher humidity.

### CLEAN UP AND STORAGE

- Use soap and water. Properly dispose of all soiled rags and protect unused product from freezing.
- To recycle or properly dispose of paint in your community call 1-800-CLEANUP or visit [www.Earth911.org](http://www.Earth911.org).

† **WARNING!** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

**WARNING!** Sanding or scraping pressure treated lumber may be hazardous; wear appropriate protection.

**WARNING!** This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

**WARNING! IRRITANT! HARMFUL IF SWALLOWED. CONTAINS: ETHYLENE GLYCOL. MAY CAUSE EYE, NOSE AND THROAT IRRITATION. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING OF VAPORS AND SPRAY MIST. WEAR EYE PROTECTION AND PROTECTIVE CLOTHING. USE ONLY WITH ADEQUATE VENTILATION.** To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air. If properly used, a respirator (NIOSH approved for organic vapor with P series particulate pre-filter) may offer additional protection; obtain professional advice before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. **FIRST AID:** If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

**CAUTION: KEEP OUT OF REACH OF CHILDREN - DO NOT TAKE INTERNALLY.**