

WORKPLACE/OCCUPATIONAL RESPIRATOR APPLICATION GUIDE



Always read and follow all user instructions

For additional information to help you select appropriate 3M™ Respirators for your workplace, including a list of applicable airborne contaminants, please visit: [3M.com/respiratorselector](https://www.3m.com/respiratorselector)

POTENTIAL APPLICATIONS

WOODWORKING

	N95	R95 Nuisance Level Acid Gas Odor ¹ Relief	R95 Nuisance Level Organic Vapor Odor ¹ Relief	N95	N95 Welding	P95 Nuisance Organic Vapor Odor ¹ Relief	N100 Lead	OV/P95	OV/P95 Full Face	P100 Lead & Mold Nuisance Organic Vapor Odor ¹ Relief	P100 Lead Paint	OV/P100	OV/AG/P100
Painting			Nuisance Level Odor ¹					X	X			X	X
Sanding, Sawing, Lathing, Routing, Drilling	X	X	X	X	X	X	X	X	X	X	X	X	X
Varnish, Staining			Nuisance Level Odor ¹			Nuisance Level Odor ¹		X	X	Nuisance Level Odor ¹		X	X
Certain Cleaning Solvents (like paint thinner and mineral spirits)			Nuisance Level Odor ¹			Nuisance Level Odor ¹		X	X	Nuisance Level Odor ¹		X	X
Glues			Nuisance Level Odor ¹			Nuisance Level Odor ¹		X	X	Nuisance Level Odor ¹		X	X

CUSTODIAL

Dust from Basement, Garage, etc.	X	X	X	X	X	X	X	X	X	X	X	X	X
Fireplace Cleaning			X			X		X	X	X		X	X
Cleaners - Bleach		Nuisance Level Odor ¹											X
Window Cleaner, Floor Cleaner (solvent-based only)			Nuisance Level Odor ¹			Nuisance Level Odor ¹		X	X	Nuisance Level Odor ¹		X	X
Sweeping, Vacuuming	X	X	X	X	X	X	X	X	X	X	X	X	X
Pool/Hot Tub Cleaning, Chlorinated Materials													X
Rust Removal with Acid-based Solution													X

ABATEMENT

Mold Removal - Dry Removal ³	X	X	X	X	X	X	X	X	X	X	X	X	X
Mold Removal - Bleach ³		Nuisance Level Odor ¹											X

REMODELING AND REPAIR

Cement Mixing ²	See www.OSHA.gov or Call 3M at 1-800-243-4630												
Cutting or Sanding Sheetrock/ Drywall/ Plaster ²	X	X	X	X	X	X	X	X	X	X	X	X	X
Driveway Resealing			Nuisance Level Odor ¹			Nuisance Level Odor ¹		X	X	Nuisance Level Odor ¹		X	X
Installing Fiberglass Insulation	X	X	X	X	X	X	X	X	X	X	X	X	X
Insulation (spray foam) ⁴								X	X			X	X
Coatings (powder)	X	X	X	X	X	X	X	X	X	X	X	X	X
Cutting Brick/Pavers, Stone Dust, Brick Dust ²	See www.OSHA.gov or Call 3M at 1-800-243-4630												
Metalworking, Welding, Soldering, Grinding, Torch Cutting					X					X	X		
Concrete Polishing ²	See www.OSHA.gov or Call 3M at 1-800-243-4630												
Sanding Wood, Plastic, Metal	X	X	X	X	X	X	X	X	X	X	X	X	X

GROUNDSKEEPING

Fertilizing (dry or certain sprays)	X	X	X	X	X	X	X	X	X	X	X	X	X
Lawn Mowing, Grass Clippings, Leaf Blowing, Mulching Bark/Leaves	X	X	X	X	X	X	X	X	X	X	X	X	X
Pesticides, Mixing and Applying	Refer to Pesticide Product Label for Respirator Guidance or call 3M at 1-800-243-4630												
Garbage Composting			Nuisance Level Odor ¹			Nuisance Level Odor ¹		X	X	Nuisance Level Odor ¹		X	X
Pollen	X	X	X	X	X	X	X	X	X	X	X	X	X

PAINTING

Latex Paint			Nuisance Level Odor ¹			Nuisance Level Odor ¹		X	X	Nuisance Level Odor ¹		X	X
Oil-based Paints, Lacquers, Enamels			Nuisance Level Odor ¹			Nuisance Level Odor ¹		X	X	Nuisance Level Odor ¹		X	X
Automotive Spray Paint ⁴								X	X			X	X
Paint Spraying								X	X			X	X

SPECIAL CONSIDERATIONS

Asbestos Removal, Lead-based Paint Removal, Cement Mixing ² , Concrete Polishing ² , Cutting Brick/Pavers ² , Stone Dust ² , Brick Dust ²	See www.OSHA.gov or call 3M 1-800-243-4630												
--	--	--	--	--	--	--	--	--	--	--	--	--	--

¹ For nuisance-level odors only. Nuisance level refers to concentrations not exceeding the OSHA PEL or applicable government occupational exposure limits, whichever is lower.

² See Silica Standard OSHA.gov

³ For area less than 100 sq./feet-Follow EPA Guidelines for mold removal: epa.gov/mold

⁴ Not for use with isocyanates in Canada

FOR US AND CANADA ONLY



Warning: Respirators help protect against certain airborne contaminants. Before use, the wearer must read and understand the User Instructions provided as a part of the product packaging. Follow all local regulations. In the U.S., a written respiratory protection program must be implemented meeting all the requirements of OSHA 29 CFR 1910.134 including training, fit testing and medical evaluation. In Canada, CSA standards Z94.4 requirements must be met and/or requirements of the applicable jurisdiction, as appropriate. Misuse may result in sickness or death. For correct use, consult supervisor and User Instructions, or call 3M Personal Safety Division (PSD) Technical Service in the U.S.A. at 1-800-243-4630. In Canada, call 1-800-267-4414.

